



**THE DATASHEET OF  
AP432SAG-7**



## Description


The AP432 and AP432A are 3-terminal adjustable precision shunt regulators with guaranteed stable temperature over the applicable extended commercial temperature range. The output voltage may be set at any level greater than 1.24V ( $V_{REF}$ ) up to 20V merely by selecting two external resistors that act as a voltage divider network. These devices have a typical output impedance of 0.2Ω. Active output circuitry provides very sharp turn-on characteristics, making these devices excellent improved replacements for Zener diodes in many applications.

The precise +/-1% reference voltage tolerance of the AP432/AP432A make it possible in many applications to avoid the use of a variable resistor, consequently saving cost and eliminating drift and reliability problems associated with it.

## Features


- Precision Reference Voltage
  - AP432 : 1.24V ± 1%
  - AP432A : 1.24V ± 0.5%
- Sink Current Capability: 200mA
- Minimum Cathode Current for Regulation: 150µA
- Equivalent Full-Range Temp Coefficient: 30 ppm/°C
- Fast Turn-On Response
- Low Dynamic Output Impedance: 0.2Ω
- Programmable Output Voltage to 20V
- Low Output Noise
- Lead Free packages: SOT25, SC59, SC59R and SOT89-3
  - **Lead-Free Finish; RoHS Compliant (Notes 1 & 2)**
- SOT23, SOT23R, SOT25, SC59, SC59R, SO-8 and SOT89: Available in "Green" Molding Compound (No Br, Sb)
  - **Halogen and Antimony Free. "Green" Device (Note 3)**

## Pin Assignments




- Notes:
1. EU Directive 2002/95/EC (RoHS) & 2011/65/EU (RoHS 2) compliant. All applicable RoHS exemptions applied.
  2. See <http://www.diodes.com> for more information about Diodes Incorporated's definitions of Halogen- and Antimony-free, "Green" and Lead-free.
  3. Halogen- and Antimony-free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.


## Typical Applications Circuit



**Functional Block Diagram**



**Functional Block Diagram**




**Absolute Maximum Ratings** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Symbol           | Parameter                         | Rating      | Unit |    |
|------------------|-----------------------------------|-------------|------|----|
| V <sub>CV</sub>  | Cathode Voltage                   | 20          | V    |    |
| I <sub>CC</sub>  | Continuous Cathode Current        | -10 to +250 | mA   |    |
| I <sub>REF</sub> | Reference Input Current           | 10          | mA   |    |
| T <sub>OP</sub>  | Operating Temperature             | -20 to +85  | °C   |    |
| T <sub>ST</sub>  | Storage Temperature               | -65 to +150 | °C   |    |
| P <sub>D</sub>   | Power Dissipation<br>(Notes 4, 5) | SOT23(R)    | 400  | mW |
|                  |                                   | SOT25       | 550  | mW |
|                  |                                   | SC59(R)     | 400  | mW |
|                  |                                   | SO-8        | 600  | mW |
|                  |                                   | SOT89-3     | 800  | mW |

Notes: 4. T<sub>J</sub>, max = +150°C.  
5. Ratings apply to ambient temperature at +25°C.

**Electrical Characteristics** (@T<sub>A</sub> = +25°C, unless otherwise specified.)

| Symbol                                 | Parameter   | Test Conditions   |   | Min            | Typ  | Max            | Unit |
|--|---|---|---|----------------|------|----------------|------|
| V <sub>REF</sub>                       | Reference voltage   | V <sub>KA</sub> = V <sub>REF</sub> ,<br>I <sub>KA</sub> = 10mA (Figure 1)   | AP432<br>AP432A                         | 1.227<br>1.233 | 1.24 | 1.252<br>1.246 | V    |
| V <sub>REF</sub>                       | Deviation of reference input voltage over temperature (Note 4)            | V <sub>KA</sub> = V <sub>REF</sub> , I <sub>KA</sub> = 10mA,<br>T <sub>A</sub> = Full range (Figure 1)                                  |   | —              | 3.0  | 20             | mV   |
| $\frac{\Delta V_{REF}}{\Delta V_{KA}}$ | Ratio of the change in reference voltage to the change in cathode voltage | I <sub>KA</sub> = 10mA (Figure 2)   | V <sub>KA</sub> = 20 ~ V <sub>REF</sub> | —              | -1.4 | -2.0           | mV/V |
| I <sub>REF</sub>                       | Reference input current   | R1 = 10KΩ, R2 = ∞ I <sub>KA</sub> = 10mA (Figure 2)   |   | —              | 1.4  | 3.5            | μA   |
| αI <sub>REF</sub>                      | Deviation of reference input current over temperature                     | R1 = 10KΩ, R2 = ∞ I <sub>KA</sub> = 10mA<br>T <sub>A</sub> = Full range (Figure 2)  |   | —              | 0.4  | 1.2            | μA   |
| I <sub>KA(MIN)</sub>                   | Minimum cathode current for regulation                                    | V <sub>KA</sub> = V <sub>REF</sub> (Figure 1)   |   | —              | 0.15 | 0.3            | mA   |
| I <sub>KA(OFF)</sub>                   | Off-state current   | V <sub>KA</sub> = 36V, V <sub>REF</sub> = 0V (Figure 3)   |   | —              | 0.1  | 1.0            | μA   |
| Z <sub>KA</sub>                        | Dynamic output impedance (Note 5)   | V <sub>KA</sub> = V <sub>REF</sub> V <sub>KA</sub> = V <sub>REF</sub><br>ΔI <sub>KA</sub> = 0.1mA ~ 15mA<br>Frequency ≤ 1KHz (Figure 1) |   | —              | 0.2  | 0.5            | Ω    |



Notes: 6. Deviation of reference input voltage, V<sub>DEV</sub>, is defined as the maximum variation of the reference over the full temperature range. The average temperature coefficient of the reference input voltage αV<sub>REF</sub> is defined as:

$$|\alpha V_{REF}| = \frac{\left(\frac{V_{DEV}}{V_{REF}(25^{\circ}C)}\right) \cdot 10^6}{T_2 - T_1} \dots \dots \dots \text{(ppm/}^{\circ}\text{C)}$$

Where:

T<sub>2</sub> – T<sub>1</sub> = full temperature change.

αV<sub>REF</sub> can be positive or negative depending on whether the slope is positive or negative.

Notes: 7. The dynamic output impedance, Z<sub>z</sub>, is defined as:

$$|Z_{KA}| = \frac{\Delta V_{KA}}{\Delta I_{KA}}$$

When the device is programmed with two external resistors R1 and R2 (see Figure 2.), the dynamic output impedance of the overall circuit, is defined as:

$$|Z_{KA}'| = \frac{\Delta V}{\Delta I} \approx |Z_{KA}| \left(1 + \frac{R1}{R2}\right)$$

**Test Circuits**





Fig 1. Test Circuit for  $V_{KA} = V_{REF}$



Note:  $V_{KA} = V_{REF}(1 + R1/R2) + I_{REF} \times R1$

Fig 2. Test Circuit for  $V_{KA} > V_{REF}$








Fig 3. Test Circuit for Off-State Current



**Typical Performance Characteristics**





**Typical Performance Characteristics (cont.)**




Test Circuit for Voltage Amplification



Test Circuit for Reference Impedance



Test Circuit for Curve A



Test Circuit for Curve B, C, and D

†The areas under the curves represent conditions that may cause the device to oscillate. For curves B, C, and D, R2 and V+ were adjusted to establish the initial V<sub>KA</sub> and I<sub>KA</sub> conditions with C<sub>L</sub>=0. V<sub>BATT</sub> and C<sub>L</sub> were then adjusted to determine the ranges of stability.

**Application Examples**

LED on when Low Limit  $< V_{IN} <$  High Limit  
 Low Limit  $\approx V_{REF} (1 + R1B/R2B)$   
 High Limit  $\approx V_{REF} (1 + R1A/R2A)$

**Fig. 4 Voltage Monitor**

Delay =  $RC \times \ln \left( \frac{V_{IN}}{V_{IN} - V_{REF}} \right)$

**Fig. 5 Delay Timer**

$I_{OUT} = V_{REF} / R_{CL}$

**Fig. 6 Current Limiter or Current Source**

$I_{OUT} = V_{REF} / R_S$

**Fig. 7 Constant-Current Sink**

$V_{OUT} = (1 + R1/R2) \times V_{REF}$

**Fig. 8 Higher-Current Shunt Regulator**

LIMIT  $\approx (1 + R1/R2) \times V_{REF}$


**Fig. 9 Crow Bar**

Output ON when Low Limit  $< V_{IN} <$  High Limit

Low Limit  $\approx V_{REF} (1 + R1B/R2B) + V_{BE}$   
 High Limit  $\approx V_{REF} (1 + R1A/R2A)$

**Fig. 10 Over-Voltage / Under-Voltage Protection Circuit**

## Ordering Information




| Part Number (Note 10) | Package Code | Packaging | 7"/13 Tape and Reel |                    | Ammo Box |                    |
|-----------------------|--------------|-----------|---------------------|--------------------|----------|--------------------|
|                       |              |           | Quantity            | Part Number Suffix | Quantity | Part Number Suffix |
| AP432(A)SAG-7         | SA           | SOT23     | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)SRG-7         | SR           | SOT23R    | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)QL-7          | Q            | SOT25     | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)QG-7          | Q            | SOT25     | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)WL-7          | W            | SC59      | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)WG-7          | W            | SC59      | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)RL-7          | R            | SC59R     | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)RG-7          | R            | SC59R     | 3000/Tape & Reel    | -7                 | NA       | NA                 |
| AP432(A)G-13          |              | SO-8      | 2500/Tape & Reel    | -13                | NA       | NA                 |
| AP432(A)YL-13         | Y            | SOT89-3   | 2500/Tape & Reel    | -13                | NA       | NA                 |
| AP432(A)YG-13         | Y            | SOT89-3   | 2500/Tape & Reel    | -13                | NA       | NA                 |
| AP432(A)YG-13R        | Y            | SOT89-3   | 2500/Tape & Reel    | -13R               | NA       | NA                 |

Notes: 8. SO-8, SOT23 and SOT23R are available in "Green" products only.  
9. Suffix "A" denotes AP432A device.

## Marking Information

(1) SC59 and SC59R


( Top View )



XX : Identification code  
Y : Year 0~9  
W : Week : A~Z : 1~26 week;  
 a~z : 27~52 week; z represents  
 52 and 53 week  
X : A~Z : Green  
 a~z : Lead Free

(2) SOT23 and SOT23R


( Top View )



XX : Identification code  
Y : Year 0~9  
W : Week : A~Z : 1~26 week;  
 a~z : 27~52 week; z represents  
 52 and 53 week  
X : A~Z : Green

(3) SOT25


( Top View )



XX : Identification code  
Y : Year 0~9  
W : Week : A~Z : 1~26 week;  
 a~z : 27~52 week; z represents  
 52 and 53 week  
X : A~Z : Green  
 a~z : Lead Free

(4) SO-8


( Top View )



G : Green  
YY : Year : 08, 09, 10~  
WW : Week : 01~52; 52  
 represents 52 and 53 week  
X : Internal Code

(5) SOT89-3

( Top View )



XX : Identification code  
Y : Year : 0~9  
W : Week : A~Z : 1~26 week;  
           a~z : 27~52 week;  
           z represents 52 and 53 week  
X : Internal code  
       A~Z : Green  
       a~z : Lead Free


| Device   | Package (Note 11) | Identification Code | Date Code |
|----------|-------------------|---------------------|-----------|
| AP432SA  | SOT23             | D3                  | YM        |
| AP432ASA | SOT23             | D4                  | YM        |
| AP432SR  | SOT23R            | D7                  | YM        |
| AP432ASR | SOT23R            | D8                  | YM        |
| AP432Q   | SOT25             | B7                  | YM        |
| AP432AQ  | SOT25             | B8                  | YM        |
| AP432W   | SC59              | B3                  | YM        |
| AP432AW  | SC59              | B4                  | YM        |
| AP432R   | SC59R             | B5                  | YM        |
| AP432AR  | SC59R             | B6                  | YM        |
| AP432Y   | SOT89             | B1                  | YM        |
| AP432AY  | SOT89             | B2                  | YM        |

Notes: 10. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Package Outline Dimensions** (All dimensions in mm.)


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.

**(1) SOT25**




| SOT25                |       |      |      |
|----------------------|-------|------|------|
| Dim                  | Min   | Max  | Typ  |
| A                    | 0.35  | 0.50 | 0.38 |
| B                    | 1.50  | 1.70 | 1.60 |
| C                    | 2.70  | 3.00 | 2.80 |
| D                    | —     | —    | 0.95 |
| H                    | 2.90  | 3.10 | 3.00 |
| J                    | 0.013 | 0.10 | 0.05 |
| K                    | 1.00  | 1.30 | 1.10 |
| L                    | 0.35  | 0.55 | 0.40 |
| M                    | 0.10  | 0.20 | 0.15 |
| N                    | 0.70  | 0.80 | 0.75 |
| α                    | 0°    | 8°   | —    |
| All Dimensions in mm |       |      |      |

**(2) SC59 and SC59R**



| SC59                 |       |      |      |
|----------------------|-------|------|------|
| Dim                  | Min   | Max  | Typ  |
| A                    | 0.35  | 0.50 | 0.38 |
| B                    | 1.50  | 1.70 | 1.60 |
| C                    | 2.70  | 3.00 | 2.80 |
| D                    | -     | -    | 0.95 |
| G                    | -     | -    | 1.90 |
| H                    | 2.90  | 3.10 | 3.00 |
| J                    | 0.013 | 0.10 | 0.05 |
| K                    | 1.00  | 1.30 | 1.10 |
| L                    | 0.35  | 0.55 | 0.40 |
| M                    | 0.10  | 0.20 | 0.15 |
| N                    | 0.70  | 0.80 | 0.75 |
| α                    | 0°    | 8°   | -    |
| All Dimensions in mm |       |      |      |

**(3) SOT23 and SOT23R**




| SOT23                |       |      |       |
|----------------------|-------|------|-------|
| Dim                  | Min   | Max  | Typ   |
| A                    | 0.37  | 0.51 | 0.40  |
| B                    | 1.20  | 1.40 | 1.30  |
| C                    | 2.30  | 2.50 | 2.40  |
| D                    | 0.89  | 1.03 | 0.915 |
| F                    | 0.45  | 0.60 | 0.535 |
| G                    | 1.78  | 2.05 | 1.83  |
| H                    | 2.80  | 3.00 | 2.90  |
| J                    | 0.013 | 0.10 | 0.05  |
| K                    | 0.903 | 1.10 | 1.00  |
| K1                   | -     | -    | 0.400 |
| L                    | 0.45  | 0.61 | 0.55  |
| M                    | 0.085 | 0.18 | 0.11  |
| α                    | 0°    | 8°   | -     |
| All Dimensions in mm |       |      |       |

**Package Outline Dimensions (cont.) (All dimensions in mm.)**


Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.

**(4) SO-8**



| SO-8                 |          |      |
|----------------------|----------|------|
| Dim                  | Min      | Max  |
| A                    | -        | 1.75 |
| A1                   | 0.10     | 0.20 |
| A2                   | 1.30     | 1.50 |
| A3                   | 0.15     | 0.25 |
| b                    | 0.3      | 0.5  |
| D                    | 4.85     | 4.95 |
| E                    | 5.90     | 6.10 |
| E1                   | 3.85     | 3.95 |
| e                    | 1.27 Typ |      |
| h                    | -        | 0.35 |
| L                    | 0.62     | 0.82 |
| θ                    | 0°       | 8°   |
| All Dimensions in mm |          |      |

**(5) SOT89-3**



| SOT89                |          |      |
|----------------------|----------|------|
| Dim                  | Min      | Max  |
| A                    | 1.40     | 1.60 |
| B                    | 0.44     | 0.62 |
| B1                   | 0.35     | 0.54 |
| C                    | 0.35     | 0.44 |
| D                    | 4.40     | 4.60 |
| D1                   | 1.62     | 1.83 |
| E                    | 2.29     | 2.60 |
| e                    | 1.50 Typ |      |
| H                    | 3.94     | 4.25 |
| H1                   | 2.63     | 2.93 |
| L                    | 0.89     | 1.20 |
| All Dimensions in mm |          |      |

Please see AP02002 at <http://www.diodes.com/datasheets/ap02002.pdf> for latest version.

NOT RECOMMENDED  
FOR NEW DESIGN


---

## Suggested Pad Layout

---


Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

**(1) SOT25**




| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 3.20          |
| G          | 1.60          |
| X          | 0.55          |
| Y          | 0.80          |
| C1         | 2.40          |
| C2         | 0.95          |

**(2) SC59 and SC59R**




| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 3.4           |
| X          | 0.8           |
| Y          | 1.0           |
| C          | 2.4           |
| E          | 1.35          |

**(3) SOT23 and SOT23R**



| Dimensions | Value (in mm) |
|------------|---------------|
| Z          | 2.9           |
| X          | 0.8           |
| Y          | 0.9           |
| C          | 2.0           |
| E          | 1.35          |

**(4) SO-8**




| Dimensions | Value (in mm) |
|------------|---------------|
| X          | 0.60          |
| Y          | 1.55          |
| C1         | 5.4           |
| C2         | 1.27          |

**Suggested Pad Layout (cont.)**

Please see AP02001 at <http://www.diodes.com/datasheets/ap02001.pdf> for the latest version.

(5) SOT89-3



| Dimensions | Value (in mm) |
|------------|---------------|
| X          | 0.900         |
| X1         | 1.733         |
| X2         | 0.416         |
| Y          | 1.300         |
| Y1         | 4.600         |
| Y2         | 1.475         |
| Y3         | 0.950         |
| Y4         | 1.125         |
| C          | 1.500         |

NOT RECOMMENDED FOR NEW DESIGN

**IMPORTANT NOTICE**

DIODES INCORPORATED MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, WITH REGARDS TO THIS DOCUMENT, INCLUDING, BUT NOT LIMITED TO, THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION).

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to this document and any product described herein. Diodes Incorporated does not assume any liability arising out of the application or use of this document or any product described herein; neither does Diodes Incorporated convey any license under its patent or trademark rights, nor the rights of others. Any Customer or user of this document or products described herein in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on Diodes Incorporated website, harmless against all damages.

Diodes Incorporated does not warrant or accept any liability whatsoever in respect of any products purchased through unauthorized sales channel. Should Customers purchase or use Diodes Incorporated products for any unintended or unauthorized application, Customers shall indemnify and hold Diodes Incorporated and its representatives harmless against all claims, damages, expenses, and attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized application.

Products described herein may be covered by one or more United States, international or foreign patents pending. Product names and markings noted herein may also be covered by one or more United States, international or foreign trademarks.

**LIFE SUPPORT**

Diodes Incorporated products are specifically not authorized for use as critical components in life support devices or systems without the express written approval of the Chief Executive Officer of Diodes Incorporated. As used herein:

- A. Life support devices or systems are devices or systems which:
  - 1. are intended to implant into the body, or
  - 2. support or sustain life and whose failure to perform when properly used in accordance with instructions for use provided in the labeling can be reasonably expected to result in significant injury to the user.
- B. A critical component is any component in a life support device or system whose failure to perform can be reasonably expected to cause the failure of the life support device or to affect its safety or effectiveness.

Customers represent that they have all necessary expertise in the safety and regulatory ramifications of their life support devices or systems, and acknowledge and agree that they are solely responsible for all legal, regulatory and safety-related requirements concerning their products and any use of Diodes Incorporated products in such safety-critical, life support devices or systems, notwithstanding any devices- or systems-related information or support that may be provided by Diodes Incorporated. Further, Customers must fully indemnify Diodes Incorporated and its representatives against any damages arising out of the use of Diodes Incorporated products in such safety-critical, life support devices or systems.

Copyright © 2012, Diodes Incorporated

[www.diodes.com](http://www.diodes.com)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View AP432SAG-7 on WIN SOURCE](#)
- ⊖ [Diodes Incorporated Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management