



**THE DATASHEET OF
TE10A2402C01**




WE POWER WHAT MATTERS

<p>No.00</p>  <ul style="list-style-type: none"> Need a different connector, cable size, product markings? Let SL Power help customize your power supply. Contact us at 1-800-235-5929, or at info@slpower.com 	<p>No.02</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 9.5mm straight barrel plug - Center Positive 	<p>No.03</p>  <ul style="list-style-type: none"> 2.5 x 5.5 x 9.5mm straight barrel plug Center Positive (Standard Models) 	<p>No.12</p>  <ul style="list-style-type: none"> 5 pin DIN-180 male connector (Pins 3, 5 = (+), pins 1, 2, 4 = (-)) 	<p>No.22</p>  <ul style="list-style-type: none"> 6 pin DIN male connector (Pins 1, 2 = (+), pins 4, 5 = (-)) 	<p>No.23</p>  <ul style="list-style-type: none"> 8 pin DIN male connector (Pins 3, 7 = (+), pins 1, 4, 6, 8 = (-), shell = FG))
<p>No.32</p>  <ul style="list-style-type: none"> 9 pin "D" type, female (Pin 8 = (+), pin 5 = (-), all others = NC) 	<p>No.33</p>  <ul style="list-style-type: none"> 2.5 x 5.5 x 12.5mm straight barrel plug - Center Positive 	<p>No.40</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 9.5mm right angle barrel plug (high retention) Center Positive 	<p>No.41</p>  <ul style="list-style-type: none"> 2.5 x 5.5 x 9.5mm right angle barrel plug (high retention) Center Positive 	<p>No.42</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 11mm straight barrel plug (high retention) Center Positive 	<p>No.43</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 11mm straight barrel plug (high retention) Center Positive
<p>No.44</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 9.5mm straight barrel plug, locking - Center Positive 	<p>No.45</p>  <ul style="list-style-type: none"> 902.5 x 5.5 x 9.5mm straight barrel plug, locking Center Positive 	<p>No.48</p>  <ul style="list-style-type: none"> 3 pin Snap n Lock, Kycon Kpp-3P or equivalent (Pin 1 = (+), pin 2 = (-)) 	<p>No.49</p>  <ul style="list-style-type: none"> 4 pin Snap n Lock, Kycon Kpp-4P or equivalent (Pins 1, 3 = (+), pins 2, 4 = (-)) 	<p>No.51</p>  <ul style="list-style-type: none"> 6 pin Minifit - Molex 39-01-2060 or equivalent (Pins 1, 4 = (+), pins 3, 6 = (-)) 	<p>No.65</p>  <ul style="list-style-type: none"> Stripped and Tinned Leads
<p>No.70</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 11mm right angle barrel plug (high retention) Center Positive 	<p>No.71</p>  <ul style="list-style-type: none"> 2.5 x 5.5 x 11mm right angle barrel plug (high retention) Center Positive 	<p>No.72</p>  <ul style="list-style-type: none"> 2.1 x 5.5 x 9.5mm straight barrel plug (high retention, no spark) Center Positive 	<p>No.73</p>  <ul style="list-style-type: none"> 2.5 x 5.5 x 9.5mm straight barrel plug (high retention, no spark) Center Positive 	<p>No.74</p>  <ul style="list-style-type: none"> EIAJ#5 style connector Center Positive 	<p>No.99</p>  <ul style="list-style-type: none"> Micro USB Pin 1 = (+), pin 5 = RTN, pins 2, 3, 4 = NC

These standard output connectors are available for our ME and TE series external power supplies. SL Power has the capability of incorporating other types of output connectors for unique and specific applications. Choosing the right output connector is dependent upon many variables and our team is readily available to provide professional support and guidance: info@slpower.com





Medical



Test & Measurement



Industrial



LED



Audio Visual



ITE & Comms



Renewable



Military COTS



Display & Signage



Automation



Broadcast



Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View TE10A2402C01 on WIN SOURCE](#)
- [SL Power Electronics Manufacture of Condor/Ault Brands Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management