




# THE DATASHEET OF OPA4244EA/250G4





**OPA244**  
**OPA2244**  
**OPA4244**

## MicroPower, Single-Supply OPERATIONAL AMPLIFIERS MicroAmplifier™ Series

### FEATURES

- **MicroSIZE PACKAGES**  
 OPA244 (Single): SOT-23-5  
 OPA2244 (Dual): MSOP-8  
 OPA4244 (Quad): TSSOP-14
- **MicroPOWER:**  $I_Q = 50\mu\text{A}/\text{channel}$
- **SINGLE SUPPLY OPERATION**
- **WIDE BANDWIDTH:** 430kHz
- **WIDE SUPPLY RANGE:**  
 Single Supply: 2.2V to 36V  
 Dual Supply:  $\pm 1.1\text{V}$  to  $\pm 18\text{V}$

### APPLICATIONS


- **BATTERY POWERED SYSTEMS**
- **PORTABLE EQUIPMENT**
- **PCMCIA CARDS**
- **BATTERY PACKS AND POWER SUPPLIES**
- **CONSUMER PRODUCTS**

### DESCRIPTION

The OPA244 (single), OPA2244 (dual), and OPA4244 (quad) op amps are designed for very low quiescent current ( $50\mu\text{A}/\text{channel}$ ), yet achieve excellent bandwidth. Ideal for battery powered and portable instrumentation, all versions are offered in micro packages for space-limited applications. The dual and quad versions feature completely independent circuitry for lowest crosstalk and freedom from interaction, even when overdriven or overloaded.

The OPA244 series is easy to use and free from phase inversion and overload problems found in some other op amps. These amplifiers are stable in unity gain and excellent performance is maintained as they swing to their specified limits. They can be operated from single (+2.2V to +36V) or dual supplies ( $\pm 1.1\text{V}$  to  $\pm 18\text{V}$ ). The input common-mode voltage range includes ground—ideal for many single supply applications. All versions have similar performance. However, there are some differences, such as common-mode rejection. All versions are interchangeable in most applications.

All versions are offered in miniature, surface-mount packages. OPA244 (single version) comes in the tiny 5-lead SOT-23-5 surface mount, SO-8 surface mount, and 8-pin DIP. OPA2244 (dual version) is available in the MSOP-8 surface mount, SO-8 surface-mount, and 8-pin DIP. The OPA4244 (quad) comes in the TSSOP-14 surface mount. They are fully specified from  $-40^\circ\text{C}$  to  $+85^\circ\text{C}$  and operate from  $-55^\circ\text{C}$  to  $+125^\circ\text{C}$ . A SPICE Macromodel is available for design analysis.



International Airport Industrial Park • Mailing Address: PO Box 11400, Tucson, AZ 85734 • Street Address: 6730 S. Tucson Blvd., Tucson, AZ 85706 • Tel: (520) 746-1111  
 Twx: 910-952-1111 • Internet: <http://www.burr-brown.com/> • Cable: BBRCORP • Telex: 066-6491 • FAX: (520) 889-1510 • Immediate Product Info: (800) 548-6132

# SPECIFICATIONS: $V_S = +2.6V$ to $+36V$

**Boldface** limits apply over the specified temperature range,  $T_A = -40^\circ\text{C}$  to  $+85^\circ\text{C}$

At  $T_A = +25^\circ\text{C}$ ,  $R_L = 20\text{k}\Omega$  connected to ground, unless otherwise noted.

| PARAMETER   | CONDITION   | OPA244NA, PA, UA   |   |   | UNITS   |
|---|---|--|---|---|---|
|   |   | MIN  | TYP <sup>(1)</sup>  | MAX                                     |   |
| <b>OFFSET VOLTAGE</b><br>Input Offset Voltage<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>vs Temperature<br>vs Power Supply<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$  | $V_{OS}$<br>$V_S = \pm 7.5V, V_{CM} = 0$<br>$dV_{OS}/dT$<br>$PSRR$<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>$V_S = +2.6V$ to $+36V$<br>$V_S = +2.6V$ to $+36V$   |  | $\pm 0.7$<br>$\pm 4$<br>5   | $\pm 1.5$<br>$\pm 2$<br>50<br><b>50</b> | mV<br>mV<br>$\mu\text{V}/^\circ\text{C}$<br>$\mu\text{V}/V$<br>$\mu\text{V}/V$  |
| <b>INPUT BIAS CURRENT</b><br>Input Bias Current<br>Input Offset Current   | $I_B$<br>$I_{OS}$<br>$V_{CM} = V_S/2$<br>$V_{CM} = V_S/2$   |  | -10<br>$\pm 1$  | -25<br>$\pm 10$                         | nA<br>nA  |
| <b>NOISE</b><br>Input Voltage Noise, $f = 0.1\text{kHz}$ to $10\text{kHz}$<br>Input Voltage Noise Density, $f = 1\text{kHz}$<br>Current Noise Density, $f = 1\text{kHz}$  | $e_n$<br>$i_n$  |  | 0.4<br>22<br>40   |   | $\mu\text{Vp-p}$<br>$\text{nV}/\sqrt{\text{Hz}}$<br>$\text{fA}/\sqrt{\text{Hz}}$  |
| <b>INPUT VOLTAGE RANGE</b><br>Common-Mode Voltage Range<br>Common-Mode Rejection<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$   | $V_{CM}$<br>CMRR<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$  | 0<br>84<br><b>84</b>   |   | $(V+) - 0.9$                            | V<br>dB<br>dB   |
| <b>INPUT IMPEDANCE</b><br>Differential<br>Common-Mode   |   |  | $10^6 \parallel 2$<br>$10^9 \parallel 2$  |   | $\Omega \parallel \text{pF}$<br>$\Omega \parallel \text{pF}$  |
| <b>OPEN-LOOP GAIN</b><br>Open-Loop Voltage Gain<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$  | $A_{OL}$<br>$V_O = 0.5V$ to $(V+) - 0.9$<br>$V_O = 0.5V$ to $(V+) - 0.9$  | 86<br><b>86</b>  | 106   |   | dB<br>dB  |
| <b>FREQUENCY RESPONSE</b><br>Gain-Bandwidth Product<br>Slew Rate<br>Settling Time 0.01%<br>Overload Recovery Time   | GBW<br>SR<br>$G = 1$<br>10V Step<br>$V_{IN} \cdot \text{Gain} = V_S$  |  | 430<br>-0.1/+0.16<br>150<br>8   |   | kHz<br>V/ $\mu\text{s}$<br>$\mu\text{s}$<br>$\mu\text{s}$   |
| <b>OUTPUT</b><br>Voltage Output, Positive<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>Voltage Output, Negative<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>Voltage Output, Positive<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>Voltage Output, Negative<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>Short-Circuit Current<br>Capacitive Load Drive | $V_O$<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to $V_S/2$<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to $V_S/2$<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to $V_S/2$<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to $V_S/2$<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$A_{OL} \geq 80\text{dB}, R_L = 20\text{k}\Omega$ to Ground<br>$I_{SC}$<br>$C_{LOAD}$ | $(V+) - 0.9$<br><b><math>(V+) - 0.9</math></b><br>0.5<br><b>0.5</b><br>0.5<br>$(V+) - 0.75$<br>$(V+) - 0.75$<br>0.1<br><b>0.1</b><br>-25/+12 | $(V+) - 0.75$<br>$(V+) - 0.75$<br>0.2<br><b>0.2</b><br>$(V+) - 0.75$<br>$(V+) - 0.75$<br>0.1<br><b>0.1</b><br>-25/+12 |   | V<br>V<br>V<br>V<br>V<br>V<br>V<br>V<br>mA  |
| <b>POWER SUPPLY</b><br>Specified Voltage Range<br>Minimum Operating Voltage<br>Quiescent Current<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$   | $V_S$<br>$I_Q$<br>$T_A = -40^\circ\text{C}$ to $85^\circ\text{C}$<br>$I_O = 0$<br>$I_O = 0$   | <b>+2.6</b>  | +2.2<br>50  | <b>+36</b><br>60<br><b>70</b>           | V<br>V<br>$\mu\text{A}$<br>$\mu\text{A}$  |
| <b>TEMPERATURE RANGE</b><br>Specified Range<br>Operating Range<br>Storage Range<br>Thermal Resistance<br>SOT-23-5 Surface-Mount<br>SO-8 Surface-Mount<br>8-Pin DIP  | $\theta_{JA}$   | -40<br>-55<br>-65  |   | 85<br>125<br>150                        | $^\circ\text{C}$<br>$^\circ\text{C}$<br>$^\circ\text{C}$<br>$^\circ\text{C}/\text{W}$<br>$^\circ\text{C}/\text{W}$<br>$^\circ\text{C}/\text{W}$ |

NOTE: (1)  $V_S = +15V$ .

The information provided herein is believed to be reliable; however, BURR-BROWN assumes no responsibility for inaccuracies or omissions. BURR-BROWN assumes no responsibility for the use of this information, and all use of such information shall be entirely at the user's own risk. Prices and specifications are subject to change without notice. No patent rights or licenses to any of the circuits described herein are implied or granted to any third party. BURR-BROWN does not authorize or warrant any BURR-BROWN product for use in life support devices and/or systems.

# SPECIFICATIONS: $V_S = +2.6V$ to $+36V$

**Boldface** limits apply over the specified temperature range,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$

At  $T_A = +25^{\circ}C$ ,  $R_L = 20k\Omega$  connected to ground, unless otherwise noted.

| PARAMETER   | CONDITION  | OPA2244EA, PA, UA  |  |   | UNITS  |
|---|--|--|--|---|--|
|   |  | MIN  | TYP <sup>(1)</sup>   | MAX                                     |  |
| <b>OFFSET VOLTAGE</b><br>Input Offset Voltage<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>vs Temperature<br>vs Power Supply<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Channel Separation  | $V_{OS}$<br>$V_S = \pm 7.5V, V_{CM} = 0$<br>$dV_{OS}/dT$<br>$PSRR$<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>$V_S = +2.6V$ to $+36V$<br>$V_S = +2.6V$ to $+36V$  |  | $\pm 0.7$<br>$\pm 4$<br>5<br>140   | $\pm 1.5$<br>$\pm 2$<br>50<br><b>50</b> | mV<br>mV<br>$\mu V/^{\circ}C$<br>$\mu V/V$<br>$\mu V/V$<br>dB                                |
| <b>INPUT BIAS CURRENT</b><br>Input Bias Current<br>Input Offset Current   | $I_B$<br>$I_{OS}$<br>$V_{CM} = V_S/2$<br>$V_{CM} = V_S/2$  |  | -10<br>$\pm 1$   | -25<br>$\pm 10$                         | nA<br>nA   |
| <b>NOISE</b><br>Input Voltage Noise, $f = 0.1kHz$ to $10kHz$<br>Input Voltage Noise Density, $f = 1kHz$<br>Current Noise Density, $f = 1kHz$  | $e_n$<br>$i_n$   |  | 0.4<br>22<br>40  |   | $\mu Vp-p$<br>$nV/\sqrt{Hz}$<br>$fA/\sqrt{Hz}$   |
| <b>INPUT VOLTAGE RANGE</b><br>Common-Mode Voltage Range<br>Common-Mode Rejection<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$   | $V_{CM}$<br>CMRR<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$   | 0<br>72<br><b>72</b>   |  | $(V+) - 0.9$<br>98                      | V<br>dB<br>dB  |
| <b>INPUT IMPEDANCE</b><br>Differential<br>Common-Mode   |  |  | $10^6 \parallel 2$<br>$10^9 \parallel 2$   |   | $\Omega \parallel pF$<br>$\Omega \parallel pF$   |
| <b>OPEN-LOOP GAIN</b><br>Open-Loop Voltage Gain<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$  | $A_{OL}$<br>$V_O = 0.5V$ to $(V+) - 0.9$<br>$V_O = 0.5V$ to $(V+) - 0.9$   | 86<br><b>86</b>  | 106  |   | dB<br>dB   |
| <b>FREQUENCY RESPONSE</b><br>Gain-Bandwidth Product<br>Slew Rate<br>Settling Time 0.01%<br>Overload Recovery Time   | GBW<br>SR<br>$G = 1$<br>10V Step<br>$V_{IN} \cdot Gain = V_S$  |  | 430<br>$-0.1/+0.16$<br>150<br>8  |   | kHz<br>V/ $\mu s$<br>$\mu s$<br>$\mu s$  |
| <b>OUTPUT</b><br>Voltage Output, Positive<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Negative<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Positive<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Negative<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Short-Circuit Current<br>Capacitive Load Drive | $V_O$<br>$I_{SC}$<br>$C_{LOAD}$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>See Typical Curve | $(V+) - 0.9$<br><b><math>(V+) - 0.9</math></b><br>0.5<br><b>0.5</b><br>0.5<br><b>0.5</b><br>0.1<br><b>0.1</b><br>$-25/+12$ | $(V+) - 0.75$<br>$(V+) - 0.75$<br>0.2<br><b>0.2</b><br>$(V+) - 0.75$<br>$(V+) - 0.75$<br>0.1<br><b>0.1</b> |   | V<br>V<br>V<br>V<br>V<br>V<br>V<br>V<br>mA   |
| <b>POWER SUPPLY</b><br>Specified Voltage Range<br>Minimum Operating Voltage<br>Quiescent Current (per amplifier)<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$   | $V_S$<br>$I_Q$<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>$I_O = 0$<br>$I_O = 0$  | <b>+2.6</b>  | +2.2<br>40   | <b>+36</b><br>50<br><b>63</b>           | V<br>V<br>$\mu A$<br>$\mu A$   |
| <b>TEMPERATURE RANGE</b><br>Specified Range<br>Operating Range<br>Storage Range<br>Thermal Resistance<br>MSOP-8 Surface-Mount<br>SO-8 Surface-Mount<br>8-Pin DIP  | $\theta_{JA}$  | -40<br>-55<br>-65  |  | 85<br>125<br>150                        | $^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C/W$<br>$^{\circ}C/W$<br>$^{\circ}C/W$ |

NOTE: (1)  $V_S = +15V$ .

# SPECIFICATIONS: $V_S = +2.6V$ to $+36V$

**Boldface** limits apply over the specified temperature range,  $T_A = -40^{\circ}C$  to  $+85^{\circ}C$

At  $T_A = +25^{\circ}C$ ,  $R_L = 20k\Omega$  connected to ground, unless otherwise noted.

| PARAMETER   | CONDITION  | OPA4244EA  |   |   | UNITS   |
|---|--|--|---|---|---|
|   |  | MIN  | TYP <sup>(1)</sup>  | MAX                                     |   |
| <b>OFFSET VOLTAGE</b><br>Input Offset Voltage<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>vs Temperature<br>vs Power Supply<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Channel Separation  | $V_{OS}$<br>$V_S = \pm 7.5V, V_{CM} = 0$<br>$dV_{OS}/dT$<br>$PSRR$<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>$V_S = +2.6V$ to $+36V$<br>$V_S = +2.6V$ to $+36V$  |  | $\pm 0.7$<br>$\pm 4$<br>5<br>140  | $\pm 1.5$<br>$\pm 2$<br>50<br><b>50</b> | mV<br>mV<br>$\mu V/^{\circ}C$<br>$\mu V/V$<br>$\mu V/V$<br>dB |
| <b>INPUT BIAS CURRENT</b><br>Input Bias Current<br>Input Offset Current   | $I_B$<br>$I_{OS}$<br>$V_{CM} = V_S/2$<br>$V_{CM} = V_S/2$  |  | -10<br>$\pm 1$  | -25<br>$\pm 10$                         | nA<br>nA  |
| <b>NOISE</b><br>Input Voltage Noise, $f = 0.1kHz$ to $10kHz$<br>Input Voltage Noise Density, $f = 1kHz$<br>Current Noise Density, $f = 1kHz$  | $e_n$<br>$i_n$   |  | 0.4<br>22<br>40   |   | $\mu Vp-p$<br>$nV/\sqrt{Hz}$<br>$fA/\sqrt{Hz}$                |
| <b>INPUT VOLTAGE RANGE</b><br>Common-Mode Voltage Range<br>Common-Mode Rejection<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$   | $V_{CM}$<br>CMRR<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$<br>$V_S = \pm 18V, V_{CM} = -18V$ to $+17.1V$   | 0<br>82<br><b>82</b>   |   | $(V+) - 0.9$<br>104                     | V<br>dB<br>dB   |
| <b>INPUT IMPEDANCE</b><br>Differential<br>Common-Mode   |  |  | $10^6 \parallel 2$<br>$10^9 \parallel 2$  |   | $\Omega \parallel pF$<br>$\Omega \parallel pF$                |
| <b>OPEN-LOOP GAIN</b><br>Open-Loop Voltage Gain<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$  | $A_{OL}$<br>$V_O = 0.5V$ to $(V+) - 0.9$<br>$V_O = 0.5V$ to $(V+) - 0.9$   | 86<br><b>86</b>  | 106   |   | dB<br>dB  |
| <b>FREQUENCY RESPONSE</b><br>Gain-Bandwidth Product<br>Slew Rate<br>Settling Time 0.01%<br>Overload Recovery Time   | GBW<br>SR<br>$G = 1$<br>10V Step<br>$V_{IN} \cdot \text{Gain} = V_S$   |  | 430<br>$-0.1/+0.16$<br>150<br>8   |   | kHz<br>$V/\mu s$<br>$\mu s$<br>$\mu s$                        |
| <b>OUTPUT</b><br>Voltage Output, Positive<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Negative<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Positive<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Voltage Output, Negative<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>Short-Circuit Current<br>Capacitive Load Drive | $V_O$<br>$I_{SC}$<br>$C_{LOAD}$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to $V_S/2$<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>$A_{OL} \geq 80dB, R_L = 20k\Omega$ to Ground<br>See Typical Curve | $(V+) - 0.9$<br><b><math>(V+) - 0.9</math></b><br>0.5<br><b>0.5</b><br>0.5<br><b>0.5</b><br>0.1<br><b>0.1</b><br>$-25/+12$ | $(V+) - 0.75$<br>$(V+) - 0.75$<br>0.2<br><b>0.2</b><br>$(V+) - 0.75$<br>$(V+) - 0.75$<br>0.1<br><b>0.1</b><br>$-25/+12$ |   | V<br>V<br>V<br>V<br>V<br>V<br>V<br>V<br>mA                    |
| <b>POWER SUPPLY</b><br>Specified Voltage Range<br>Minimum Operating Voltage<br>Quiescent Current (per amplifier)<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$   | $V_S$<br>$I_Q$<br>$T_A = -40^{\circ}C$ to $85^{\circ}C$<br>$I_O = 0$<br>$I_O = 0$  | <b>+2.6</b>  | +2.2<br>40  | <b>+36</b><br>60<br><b>70</b>           | V<br>V<br>$\mu A$<br>$\mu A$                                  |
| <b>TEMPERATURE RANGE</b><br>Specified Range<br>Operating Range<br>Storage Range<br>Thermal Resistance<br>TSSOP-14 Surface Mount   | $\theta_{JA}$  | -40<br>-55<br>-65  |   | 85<br>125<br>150                        | $^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C$<br>$^{\circ}C/W$    |

NOTE: (1)  $V_S = +15V$ .

## ABSOLUTE MAXIMUM RATINGS<sup>(1)</sup>

|   |                            |
|---|----------------------------|
| Supply Voltage, V+ to V- .....            | 36V                        |
| Input Voltage Range <sup>(2)</sup> .....  | (V-) – 0.3V to (V+) + 0.3V |
| Input Current <sup>(2)</sup> .....        | 10mA                       |
| Output Short-Circuit <sup>(3)</sup> ..... | Continuous                 |
| Operating Temperature .....               | –55°C to +125°C            |
| Storage Temperature .....                 | –65°C to +150°C            |
| Junction Temperature .....                | 150°C                      |
| Lead Temperature (soldering, 10s) .....   | 300°C                      |
| ESD Capability .....                      | 2000V                      |

NOTES: (1) Stresses above these ratings may cause permanent damage. Exposure to absolute maximum conditions for extended periods may degrade device reliability. (2) Inputs are diode-clamped to the supply rails and should be current-limited to 10mA or less if input voltages can exceed rails by more than 0.3V. (3) Short-circuit to ground, one amplifier per package.



## ELECTROSTATIC DISCHARGE SENSITIVITY

This integrated circuit can be damaged by ESD. Burr-Brown recommends that all integrated circuits be handled with appropriate precautions. Failure to observe proper handling and installation procedures can cause damage.

ESD damage can range from subtle performance degradation to complete device failure. Precision integrated circuits may be more susceptible to damage because very small parametric changes could cause the device not to meet its published specifications.






## PACKAGE/ORDERING INFORMATION

| PRODUCT       | PACKAGE                | PACKAGE DRAWING NUMBER | SPECIFIED TEMPERATURE RANGE | PACKAGE MARKING | ORDERING NUMBER <sup>(1)</sup> | TRANSPORT MEDIA |
|---------------|------------------------|------------------------|-----------------------------|-----------------|--------------------------------|-----------------|
| <b>Single</b> |                        |                        |                             |                 |                                |                 |
| OPA244NA      | SOT-23-5 Surface-Mount | 331                    | –40°C to +85°C              | A44             | OPA244NA/250                   | Tape and Reel   |
| "             | "                      | "                      | "                           | "               | OPA244NA/3K                    | Tape and Reel   |
| OPA244PA      | 8-Pin DIP              | 006                    | –40°C to +85°C              | OPA244PA        | OPA244PA                       | Rails           |
| OPA244UA      | SO-8 Surface-Mount     | 182                    | –40°C to +85°C              | OPA244UA        | OPA244UA                       | Rails           |
| "             | "                      | "                      | "                           | "               | OPA244UA/2K5                   | Tape and Reel   |
| <b>Dual</b>   |                        |                        |                             |                 |                                |                 |
| OPA2244EA     | MSOP-8 Surface-Mount   | 337                    | –40°C to +85°C              | A44             | OPA2244EA/250                  | Tape and Reel   |
| "             | "                      | "                      | "                           | "               | OPA2244EA/2K5                  | Tape and Reel   |
| OPA2244PA     | 8-Pin DIP              | 006                    | –40°C to +85°C              | OPA2244PA       | OPA2244PA                      | Rails           |
| OPA2244UA     | SO-8 Surface-Mount     | 182                    | –40°C to +85°C              | OPA2244UA       | OPA2244UA                      | Rails           |
| "             | "                      | "                      | "                           | "               | OPA2244UA/2K5                  | Tape and Reel   |
| <b>Quad</b>   |                        |                        |                             |                 |                                |                 |
| OPA4244EA     | TSSOP-14 Surface-Mount | 357                    | –40°C to +85°C              | OPA4244EA       | OPA4244EA/250                  | Tape and Reel   |
| "             | "                      | "                      | "                           | "               | OPA4244EA/2K5                  | Tape and Reel   |

NOTE: (1) Products followed by a slash (/) are only available in Tape and Reel in the quantities indicated (e.g., /250 indicates 250 devices per reel). Ordering 3000 pieces of "OPA244NA/3K" will get a single 3000 piece Tape and Reel.







# TYPICAL PERFORMANCE CURVES

At  $T_A = 25^\circ\text{C}$ ,  $V_S = +15\text{V}$ , and  $R_L = 20\text{k}\Omega$  connected to Ground, unless otherwise noted.



# TYPICAL PERFORMANCE CURVES (Cont.)

At  $T_A = 25^\circ\text{C}$ ,  $V_S = +15\text{V}$ , and  $R_L = 20\text{k}\Omega$  connected to Ground, unless otherwise noted.




# TYPICAL PERFORMANCE CURVES (Cont.)

At  $T_A = 25^\circ\text{C}$ ,  $V_S = +15\text{V}$ , and  $R_L = 20\text{k}\Omega$  connected to Ground, unless otherwise noted.


QUIESCENT AND SHORT-CIRCUIT CURRENT vs TEMPERATURE




INPUT VOLTAGE AND CURRENT NOISE SPECTRAL DENSITY vs FREQUENCY



MAXIMUM OUTPUT VOLTAGE vs FREQUENCY



SMALL SIGNAL OVERSHOOT vs LOAD CAPACITANCE





# TYPICAL PERFORMANCE CURVES (Cont.)

At  $T_A = 25^\circ\text{C}$ ,  $V_S = +15\text{V}$ , and  $R_L = 20\text{k}\Omega$  connected to Ground, unless otherwise noted.



LARGE-SIGNAL STEP RESPONSE,  $G = 1$ ,  $C_L = 100\text{pF}$



SMALL-SIGNAL STEP RESPONSE,  $G = 1$ ,  $C_L = 100\text{pF}$



OFFSET VOLTAGE PRODUCTION DISTRIBUTION



# TYPICAL PERFORMANCE CURVES (Cont.)

At  $T_A = 25^\circ\text{C}$ ,  $V_S = +15\text{V}$ , and  $R_L = 20\text{k}\Omega$  connected to Ground, unless otherwise noted.

OFFSET VOLTAGE PRODUCTION DISTRIBUTION



# APPLICATIONS INFORMATION

The OPA244 is unity-gain stable and suitable for a wide range of general purpose applications. Power supply pins should be bypassed with 0.01µF ceramic capacitors.

## OPERATING VOLTAGE

The OPA244 can operate from single supply (+2.2V to +36V) or dual supplies (±1.1 to ±18V) with excellent performance. Unlike most op amps which are specified at only one supply voltage, the OPA244 is specified for real world applications; a single set of specifications applies throughout the +2.6V to +36V (±1.3 to ±18V) supply range.

This allows a designer to have the same assured performance at any supply voltage within this range. In addition, many key parameters are guaranteed over the specified temperature range, -40°C to +85°C. Most behavior remains unchanged throughout the full operating voltage range. Parameters which vary significantly with operating voltage or temperature are shown in typical performance curves.

Useful information on solder pad design for printed circuit boards can be found in Burr-Brown's Application Bulletin AB-132B, "Solder Pad Recommendations for Surface-Mount Devices," easily found at Burr-Brown's web site (<http://www.burr-brown.com>).



FIGURE 1. Low and High-Side Battery Current Sensing.

**PACKAGING INFORMATION**

| Orderable Device | Status<br>(1) | Package Type | Package Drawing | Pins | Package Qty | Eco Plan<br>(2)         | Lead/Ball Finish<br>(6) | MSL Peak Temp<br>(3) | Op Temp (°C) | Device Marking<br>(4/5) | Samples                 |
|------------------|---------------|--------------|-----------------|------|-------------|-------------------------|-------------------------|----------------------|--------------|-------------------------|-------------------------|
| OPA2244EA/250    | ACTIVE        | VSSOP        | DGK             | 8    | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU   CU NIPDAUAG | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA2244EA/250G4  | ACTIVE        | VSSOP        | DGK             | 8    | 250         | Green (RoHS & no Sb/Br) | CU NIPDAUAG             | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA2244EA/2K5    | ACTIVE        | VSSOP        | DGK             | 8    | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA2244EA/2K5G4  | ACTIVE        | VSSOP        | DGK             | 8    | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA2244PA        | ACTIVE        | PDIP         | P               | 8    | 50          | Green (RoHS & no Sb/Br) | CU NIPDAU               | N / A for Pkg Type   |              | OPA2244PA               | <a href="#">Samples</a> |
| OPA2244UA        | ACTIVE        | SOIC         | D               | 8    | 75          | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  |              | OPA 2244UA              | <a href="#">Samples</a> |
| OPA2244UA/2K5    | ACTIVE        | SOIC         | D               | 8    | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  |              | OPA 2244UA              | <a href="#">Samples</a> |
| OPA2244UAG4      | ACTIVE        | SOIC         | D               | 8    | 75          | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  |              | OPA 2244UA              | <a href="#">Samples</a> |
| OPA244NA/250     | ACTIVE        | SOT-23       | DBV             | 5    | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA244NA/250G4   | ACTIVE        | SOT-23       | DBV             | 5    | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA244NA/3K      | ACTIVE        | SOT-23       | DBV             | 5    | 3000        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA244NA/3KG4    | ACTIVE        | SOT-23       | DBV             | 5    | 3000        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-2-260C-1 YEAR  | -40 to 85    | A44                     | <a href="#">Samples</a> |
| OPA244UA         | ACTIVE        | SOIC         | D               | 8    | 75          | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  | -40 to 85    | OPA 244UA               | <a href="#">Samples</a> |
| OPA244UA/2K5     | ACTIVE        | SOIC         | D               | 8    | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  | -40 to 85    | OPA 244UA               | <a href="#">Samples</a> |
| OPA4244EA/250    | ACTIVE        | TSSOP        | PW              | 14   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  | -40 to 85    | OPA 4244EA              | <a href="#">Samples</a> |
| OPA4244EA/250E4  | ACTIVE        | TSSOP        | PW              | 14   | 250         | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  | -40 to 85    | OPA 4244EA              | <a href="#">Samples</a> |
| OPA4244EA/2K5    | ACTIVE        | TSSOP        | PW              | 14   | 2500        | Green (RoHS & no Sb/Br) | CU NIPDAU               | Level-3-260C-168 HR  | -40 to 85    | OPA 4244EA              | <a href="#">Samples</a> |

(1) The marketing status values are defined as follows:

**ACTIVE:** Product device recommended for new designs.

**LIFEBUY:** TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.

**NRND:** Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.

**PREVIEW:** Device has been announced but is not in production. Samples may or may not be available.

**OBSOLETE:** TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".

**RoHS Exempt:** TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.

**Green:** TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of  $\leq 1000$ ppm threshold. Antimony trioxide based flame retardants must also meet the  $\leq 1000$ ppm threshold requirement.

(3) **MSL, Peak Temp.** - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) **Lead/Ball Finish** - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

**Important Information and Disclaimer:** The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

**TAPE AND REEL INFORMATION**

**QUADRANT ASSIGNMENTS FOR PIN 1 ORIENTATION IN TAPE**


\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Reel Diameter (mm) | Reel Width W1 (mm) | A0 (mm) | B0 (mm) | K0 (mm) | P1 (mm) | W (mm) | Pin1 Quadrant |
|---------------|--------------|-----------------|------|------|--------------------|--------------------|---------|---------|---------|---------|--------|---------------|
| OPA2244EA/250 | VSSOP        | DGK             | 8    | 250  | 180.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2244EA/2K5 | VSSOP        | DGK             | 8    | 2500 | 330.0              | 12.4               | 5.3     | 3.4     | 1.4     | 8.0     | 12.0   | Q1            |
| OPA2244UA/2K5 | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA244NA/250  | SOT-23       | DBV             | 5    | 250  | 178.0              | 8.4                | 3.3     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| OPA244NA/3K   | SOT-23       | DBV             | 5    | 3000 | 178.0              | 8.4                | 3.3     | 3.2     | 1.4     | 4.0     | 8.0    | Q3            |
| OPA244UA/2K5  | SOIC         | D               | 8    | 2500 | 330.0              | 12.4               | 6.4     | 5.2     | 2.1     | 8.0     | 12.0   | Q1            |
| OPA4244EA/250 | TSSOP        | PW              | 14   | 250  | 180.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |
| OPA4244EA/2K5 | TSSOP        | PW              | 14   | 2500 | 330.0              | 12.4               | 6.9     | 5.6     | 1.6     | 8.0     | 12.0   | Q1            |

**TAPE AND REEL BOX DIMENSIONS**


\*All dimensions are nominal

| Device        | Package Type | Package Drawing | Pins | SPQ  | Length (mm) | Width (mm) | Height (mm) |
|---------------|--------------|-----------------|------|------|-------------|------------|-------------|
| OPA2244EA/250 | VSSOP        | DGK             | 8    | 250  | 210.0       | 185.0      | 35.0        |
| OPA2244EA/2K5 | VSSOP        | DGK             | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA2244UA/2K5 | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA244NA/250  | SOT-23       | DBV             | 5    | 250  | 565.0       | 140.0      | 75.0        |
| OPA244NA/3K   | SOT-23       | DBV             | 5    | 3000 | 565.0       | 140.0      | 75.0        |
| OPA244UA/2K5  | SOIC         | D               | 8    | 2500 | 367.0       | 367.0      | 35.0        |
| OPA4244EA/250 | TSSOP        | PW              | 14   | 250  | 210.0       | 185.0      | 35.0        |
| OPA4244EA/2K5 | TSSOP        | PW              | 14   | 2500 | 367.0       | 367.0      | 35.0        |

P (R-PDIP-T8)

PLASTIC DUAL-IN-LINE PACKAGE



- NOTES:
- A. All linear dimensions are in inches (millimeters).
  - B. This drawing is subject to change without notice.
  - C. Falls within JEDEC MS-001 variation BA.

DBV0005A



# PACKAGE OUTLINE

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



4214839/D 11/2018

## NOTES:

1. All linear dimensions are in millimeters. Any dimensions in parenthesis are for reference only. Dimensioning and tolerancing per ASME Y14.5M.
2. This drawing is subject to change without notice.
3. Reference JEDEC MO-178.
4. Body dimensions do not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 mm per side.

# EXAMPLE BOARD LAYOUT

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:15X



SOLDER MASK DETAILS

4214839/D 11/2018

NOTES: (continued)

- 5. Publication IPC-7351 may have alternate designs.
- 6. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

DBV0005A

SOT-23 - 1.45 mm max height

SMALL OUTLINE TRANSISTOR



SOLDER PASTE EXAMPLE  
BASED ON 0.125 mm THICK STENCIL  
SCALE:15X


4214839/D 11/2018

NOTES: (continued)

7. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
8. Board assembly site may have different recommendations for stencil design.

DGK (S-PDSO-G8)

PLASTIC SMALL-OUTLINE PACKAGE




- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0.15 per end.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0.50 per side.
  - E. Falls within JEDEC MO-187 variation AA, except interlead flash.



- NOTES:
- A. All linear dimensions are in millimeters.
  - B. This drawing is subject to change without notice.
  - C. Publication IPC-7351 is recommended for alternate designs.
  - D. Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - E. Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



4040064-3/G 02/11

- NOTES:
- A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M-1994.
  - B. This drawing is subject to change without notice.
  - C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
  - D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
  - E. Falls within JEDEC MO-153

PW (R-PDSO-G14)

PLASTIC SMALL OUTLINE



- NOTES:
- All linear dimensions are in millimeters.
  - This drawing is subject to change without notice.
  - Publication IPC-7351 is recommended for alternate designs.
  - Laser cutting apertures with trapezoidal walls and also rounding corners will offer better paste release. Customers should contact their board assembly site for stencil design recommendations. Refer to IPC-7525 for other stencil recommendations.
  - Customers should contact their board fabrication site for solder mask tolerances between and around signal pads.



D0008A

# PACKAGE OUTLINE

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



4214825/C 02/2019

NOTES:

- Linear dimensions are in inches [millimeters]. Dimensions in parenthesis are for reference only. Controlling dimensions are in inches. Dimensioning and tolerancing per ASME Y14.5M.
- This drawing is subject to change without notice.
- This dimension does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed  $.006$  [0.15] per side.
- This dimension does not include interlead flash.
- Reference JEDEC registration MS-012, variation AA.

# EXAMPLE BOARD LAYOUT

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



LAND PATTERN EXAMPLE  
EXPOSED METAL SHOWN  
SCALE:8X



SOLDER MASK DETAILS

4214825/C 02/2019

NOTES: (continued)

6. Publication IPC-7351 may have alternate designs.

7. Solder mask tolerances between and around signal pads can vary based on board fabrication site.

# EXAMPLE STENCIL DESIGN

D0008A

SOIC - 1.75 mm max height

SMALL OUTLINE INTEGRATED CIRCUIT



SOLDER PASTE EXAMPLE  
BASED ON .005 INCH [0.125 MM] THICK STENCIL  
SCALE:8X

4214825/C 02/2019

NOTES: (continued)

8. Laser cutting apertures with trapezoidal walls and rounded corners may offer better paste release. IPC-7525 may have alternate design recommendations.
9. Board assembly site may have different recommendations for stencil design.

## IMPORTANT NOTICE AND DISCLAIMER

TI PROVIDES TECHNICAL AND RELIABILITY DATA (INCLUDING DATASHEETS), DESIGN RESOURCES (INCLUDING REFERENCE DESIGNS), APPLICATION OR OTHER DESIGN ADVICE, WEB TOOLS, SAFETY INFORMATION, AND OTHER RESOURCES "AS IS" AND WITH ALL FAULTS, AND DISCLAIMS ALL WARRANTIES, EXPRESS AND IMPLIED, INCLUDING WITHOUT LIMITATION ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR NON-INFRINGEMENT OF THIRD PARTY INTELLECTUAL PROPERTY RIGHTS.

These resources are intended for skilled developers designing with TI products. You are solely responsible for (1) selecting the appropriate TI products for your application, (2) designing, validating and testing your application, and (3) ensuring your application meets applicable standards, and any other safety, security, or other requirements. These resources are subject to change without notice. TI grants you permission to use these resources only for development of an application that uses the TI products described in the resource. Other reproduction and display of these resources is prohibited. No license is granted to any other TI intellectual property right or to any third party intellectual property right. TI disclaims responsibility for, and you will fully indemnify TI and its representatives against, any claims, damages, costs, losses, and liabilities arising out of your use of these resources.

TI's products are provided subject to TI's Terms of Sale ([www.ti.com/legal/termsofsale.html](http://www.ti.com/legal/termsofsale.html)) or other applicable terms available either on [ti.com](http://ti.com) or provided in conjunction with such TI products. TI's provision of these resources does not expand or otherwise alter TI's applicable warranties or warranty disclaimers for TI products.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265  
Copyright © 2019, Texas Instruments Incorporated

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View OPA4244EA/250G4 on WIN SOURCE](#)

 [Texas Instruments](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management