






**THE DATASHEET OF**  
**28B2400-000**






SECTION A-A



DETAIL "A"  
SCALE 3:1



IMPEDANCE ( Z )			
Frequency	25 MHz	100 MHz	300 MHz
Nominal (REF)	60 Ω	135 Ω	285 Ω
Minimum	- Ω	108 Ω	- Ω



AGILENT E4991A Impedance/Material Analyzer  
HP 16092A Test Fixture, REF.3131

FERRITE CORE DIMENSIONS (SPEC):mm [Inches]

BARE DIMENSIONS		28B2400-000	
A	60.96 [2.400]	+	1.22 [.048]
B	35.56 [1.400]	+	0.71 [.028]
C	12.70 [.500]	+	0.38 [.015]

WEIGHT/1000 109.37 kgs [241.12 Lbs]

NOTES: UNLESS OTHERWISE SPECIFIED

1. COSMETIC SPECIFICATION REFER TO WI-QA-038.

DIMENSIONS ARE IN MM [INCHES].				This print is the property of Laird Tech. and is loaned in confidence subject to return upon request and with the understanding that no copies shall be made without the written consent of Laird Tech. All rights to design or invention are reserved.			
REV	DESCRIPTION	DATE	INT				
J	UPDATE COMPANY LOGO	05/22/15	QIU	PROJECT/PART NUMBER: <b>28B2400-000</b>		REV J	DRAWN BY: DJB
H	UPDATE Z SPECS AND COMPANY LOGO	06/25/04	JRK	DATE: 07/03/90	SCALE: .75:1	MATERIAL: FERRITE	
G	CHG P/N FROM 00*, REMOVE COATING SPECS	06/25/04	JRK	CAD # 28B2400-000-J	TOOL # B2400		
F	UPDATE COATING DIMS, REM FLAT from CHAMFER DETAIL, ADJUST R. DIM, UPDATE PART WGT. UPDATE Z SPECS	10/15/03	JRK				
E	UPDATE FORMAT & Z SPECS, CURVE&TOLS	07/23/03	JRK				

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View 28B2400-000 on WIN SOURCE](#)
- ⊖ [Laird-Signal Integrity Products Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management