



**THE DATASHEET OF  
SBRV640VCTT4G**



# Switch-mode Power Rectifiers

DPAK-3 Surface Mount Package

## MBRD620CT, NRVBD620VCT, SBRV620CT Series

These state-of-the-art devices are designed for use in switching power supplies, inverters and as free wheeling diodes.


### Features

- Extremely Fast Switching
- Extremely Low Forward Drop
- Platinum Barrier with Avalanche Guardrings
- NRVBD and SBRV Prefixes for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable
- These Devices are Pb-Free and are RoHS Compliant


### Mechanical Characteristics:

- Case: Epoxy, Molded
- Weight: 0.4 Gram (Approximately)
- Finish: All External Surfaces Corrosion Resistant and Terminal Leads are Readily Solderable
- Lead and Mounting Surface Temperature for Soldering Purposes: 260°C Max. for 10 Seconds
- ESD Ratings:
  - ◆ Machine Model = C
  - ◆ Human Body Model = 3B


## SCHOTTKY BARRIER RECTIFIERS 6.0 AMPERES, 20 – 60 VOLTS



DPAK  
CASE 369C



### MARKING DIAGRAM



|       |                      |
|-------|----------------------|
| A     | = Assembly Location* |
| Y     | = Year               |
| WW    | = Work Week          |
| B6x0T | = Device Code        |
| x     | = 2, 3, 4, 5, or 6   |
| G     | = Pb-Free Package    |

\* The Assembly Location Code (A) is front side optional. In cases where the Assembly Location is stamped in the package bottom (molding ejector pin), the front side assembly code may be blank.

### ORDERING INFORMATION

See detailed ordering and shipping information in the package dimensions section on page 5 of this data sheet.

NOTE: Some of the devices on this data sheet have been **DISCONTINUED**. Please refer to the table on page 5.

## MBRD620CT, NRVBD620VCT, SBRV620CT Series

### MAXIMUM RATINGS

| Rating  | Symbol                          | MBRD/NRVBD/SBRV |       |       |       |       | Unit             |
|---|---------------------------------|-----------------|-------|-------|-------|-------|------------------|
|   |                                 | 620CT           | 630CT | 640CT | 650CT | 660CT |                  |
| Peak Repetitive Reverse Voltage<br>Working Peak Reverse Voltage<br>DC Blocking Voltage                    | $V_{RRM}$<br>$V_{RWM}$<br>$V_R$ | 20              | 30    | 40    | 50    | 60    | V                |
| Average Rectified Forward Current<br>$T_C = 130^\circ\text{C}$<br>Per Diode<br>Per Device                 | $I_{F(AV)}$                     | 3<br>6          |       |       |       |       | A                |
| Peak Repetitive Forward Current,<br>$T_C = 130^\circ\text{C}$ (Square Wave, Duty = 0.5)<br>Per Diode      | $I_{FRM}$                       | 6               |       |       |       |       | A                |
| Nonrepetitive Peak Surge Current – (Surge applied at rated load conditions halfwave, single phase, 60 Hz) | $I_{FSM}$                       | 75              |       |       |       |       | A                |
| Peak Repetitive Reverse Surge Current (2 $\mu\text{s}$ , 1 kHz)   | $I_{RRM}$                       | 1               |       |       |       |       | A                |
| Operating Junction Temperature (Note 1)   | $T_J$                           | -65 to +175     |       |       |       |       | $^\circ\text{C}$ |
| Storage Temperature   | $T_{stg}$                       | -65 to +175     |       |       |       |       | $^\circ\text{C}$ |
| Voltage Rate of Change (Rated $V_R$ )   | $dv/dt$                         | 10,000          |       |       |       |       | V/ $\mu\text{s}$ |

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

1. The heat generated must be less than the thermal conductivity from Junction-to-Ambient:  $dP_D/dT_J < 1/R_{\theta JA}$ .

### THERMAL CHARACTERISTICS PER DIODE

| Characteristic   | Symbol          | Value | Unit                      |
|--|-----------------|-------|---------------------------|
| Maximum Thermal Resistance, Junction-to-Case             | $R_{\theta JC}$ | 6     | $^\circ\text{C}/\text{W}$ |
| Maximum Thermal Resistance, Junction-to-Ambient (Note 2) | $R_{\theta JA}$ | 80    | $^\circ\text{C}/\text{W}$ |

2. Rating applies when surface mounted on the minimum pad size recommended.

### ELECTRICAL CHARACTERISTICS PER DIODE

| Characteristic   | Symbol | Value                      | Unit |
|--|--------|----------------------------|------|
| Maximum Instantaneous Forward Voltage (Note 3)<br>$i_F = 3$ Amps, $T_C = 25^\circ\text{C}$<br>$i_F = 3$ Amps, $T_C = 125^\circ\text{C}$<br>$i_F = 6$ Amps, $T_C = 25^\circ\text{C}$<br>$i_F = 6$ Amps, $T_C = 125^\circ\text{C}$ | $V_F$  | 0.7<br>0.65<br>0.9<br>0.85 | V    |
| Maximum Instantaneous Reverse Current (Note 3)<br>(Rated dc Voltage, $T_C = 25^\circ\text{C}$ )<br>(Rated dc Voltage, $T_C = 125^\circ\text{C}$ )  | $i_R$  | 0.1<br>15                  | mA   |

Product parametric performance is indicated in the Electrical Characteristics for the listed test conditions, unless otherwise noted. Product performance may not be indicated by the Electrical Characteristics if operated under different conditions.

3. Pulse Test: Pulse Width = 300  $\mu\text{s}$ , Duty Cycle  $\leq 2.0\%$ .

# MBRD620CT, NRVBD620VCT, SBRV620CT Series

## TYPICAL CHARACTERISTICS





Figure 1. Typical Forward Voltage, Per Leg



\*The curves shown are typical for the highest voltage device in the voltage grouping. Typical reverse current for lower voltage selections can be estimated from these curves if  $V_R$  is sufficient below rated  $V_R$ .

Figure 2. Typical Reverse Current,\* Per Leg




Figure 3. Average Power Dissipation, Per Leg

TYPICAL CHARACTERISTICS




Figure 4. Current Derating, Case, Per Leg




Figure 5. Current Derating, Ambient, Per Leg




Figure 6. Typical Capacitance, Per Leg

## MBRD620CT, NRVBD620VCT, SBRV620CT Series

### ORDERING INFORMATION

| Device          | Package           | Shipping†          |
|-----------------|-------------------|--------------------|
| MBRD620CTT4G    | DPAK<br>(Pb-Free) | 2500 / Tape & Reel |
| MBRD640CTT4G    |                   | 2500 / Tape & Reel |
| MBRD650CTT4G    |                   | 2500 / Tape & Reel |
| MBRD660CTT4G    |                   | 2500 / Tape & Reel |
| SBRV660VCTT4G*  |                   | 2500 / Tape & Reel |
| SNRVBD660CTT4G* |                   | 2500 / Tape & Reel |

### DISCONTINUED (Note 4)

|                     |                   |                    |
|---------------------|-------------------|--------------------|
| MBRD630CTT4G        | DPAK<br>(Pb-Free) | 2500 / Tape & Reel |
| MBRD640CTG          |                   | 75 Units / Rail    |
| NRVBD640CTG*        |                   | 75 Units / Rail    |
| NRVBD640CTG-VF01*   |                   | 75 Units / Rail    |
| NRVBD640CTT4G*      |                   | 2500 / Tape & Reel |
| NRVBD640VCTT4G*     |                   | 2500 / Tape & Reel |
| SBRV640VCTT4G*      |                   | 2500 / Tape & Reel |
| MBRD650CTG          |                   | 75 Units / Rail    |
| NRVBD650CTG-VF01*   |                   | 2500 / Tape & Reel |
| NRVBD650CTT4G*      |                   | 2500 / Tape & Reel |
| NRVBD650CTT4G-VF01* |                   | 2500 / Tape & Reel |
| MBRD660CTG          |                   | 75 Units / Rail    |
| NRVBD660CTG*        |                   | 75 Units / Rail    |
| NRVBD660CTG-VF01*   |                   | 75 Units / Rail    |
| MBRD660CTRLG        |                   | 1800 / Tape & Reel |
| NRVBD660CTRLG*      |                   | 1800 / Tape & Reel |
| NRVBD660CTT4G*      |                   | 2500 / Tape & Reel |

†For information on tape and reel specifications, including part orientation and tape sizes, please refer to our Tape and Reel Packaging Specifications Brochure, BRD8011/D.

\*NRVBD and SBRV Prefixes for Automotive and Other Applications Requiring Unique Site and Control Change Requirements; AEC-Q101 Qualified and PPAP Capable.

4. **DISCONTINUED:** These devices are not recommended for new design. Please contact your **onsemi** representative for information. The most current information on these devices may be available on [www.onsemi.com](http://www.onsemi.com).



**onsemi**, **Onsemi**, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at [www.onsemi.com/site/pdf/Patent-Marking.pdf](http://www.onsemi.com/site/pdf/Patent-Marking.pdf). **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as-is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

---

## ADDITIONAL INFORMATION

### TECHNICAL PUBLICATIONS:

Technical Library: [www.onsemi.com/design/resources/technical-documentation](http://www.onsemi.com/design/resources/technical-documentation)  
onsemi Website: [www.onsemi.com](http://www.onsemi.com)

### ONLINE SUPPORT: [www.onsemi.com/support](http://www.onsemi.com/support)

For additional information, please contact your local Sales Representative at [www.onsemi.com/support/sales](http://www.onsemi.com/support/sales)

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View SBRV640VCTT4G on WIN SOURCE](#)

 [ON Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management