



# THE DATASHEET OF TSM4425CS RLG



**SOP-8**

**Pin Definition:**

- |           |          |
|-----------|----------|
| 1. Source | 8. Drain |
| 2. Source | 7. Drain |
| 3. Source | 6. Drain |
| 4. Gate   | 5. Drain |

**PRODUCT SUMMARY**

$V_{DS}$ (V)	$R_{DS(on)}$ (m $\Omega$ )	$I_D$ (A)
-30	14 @ $V_{GS} = -10V$	-11
	20 @ $V_{GS} = -4.5V$	-8.5

**Features**

- Advance Trench Process Technology
- High Density Cell Design for Ultra Low On-resistance

**Application**

- Load Switches
- Notebook PCs
- Desktop PCs

**Ordering Information**

Part No.	Package	Packing
TSM4425CS RLG	SOP-8	2.5Kpcs / 13" Reel

**Note:** "G" denotes for Halogen- and Antimony-free as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds

**Absolute Maximum Rating** ( $T_C = 25^\circ C$  unless otherwise noted)


Parameter	Symbol	Limit	Unit
Drain-Source Voltage	$V_{DS}$	-30	V
Gate-Source Voltage	$V_{GS}$	$\pm 20$	V
Continuous Drain Current	$I_D$	-11	A
Pulsed Drain Current	$I_{DM}$	-50	A
Continuous Source Current (Diode Conduction) <sup>a,b</sup>	$I_S$	-2.1	A
Maximum Power Dissipation	$P_D$	$T_a = 25^\circ C$	2.5
		$T_a = 75^\circ C$	1.6
Operating Junction Temperature	$T_J$	+150	$^\circ C$
Operating Junction and Storage Temperature Range	$T_J, T_{STG}$	- 55 to +150	$^\circ C$

**Thermal Performance**

Parameter	Symbol	Limit	Unit
Junction to Foot Thermal Resistance	$R_{\theta JF}$	18	$^\circ C/W$
Junction to Ambient Thermal Resistance (PCB mounted)	$R_{\theta JA}$	52.5	$^\circ C/W$

**Notes:**

- Pulse width limited by the Maximum junction temperature
- Surface Mounted on FR4 Board,  $t \leq 10$  sec.

**Block Diagram**



P-Channel MOSFET

### Electrical Specifications (T<sub>C</sub> = 25°C unless otherwise noted)


Parameter	Conditions	Symbol	Min	Typ	Max	Unit
<b>Static</b>						
Drain-Source Breakdown Voltage	V <sub>GS</sub> = 0V, I <sub>D</sub> = -250μA	BV <sub>DSS</sub>	-30	--	--	V
Gate Threshold Voltage	V <sub>DS</sub> = V <sub>GS</sub> , I <sub>D</sub> = -250μA	V <sub>GS(TH)</sub>	-1	--	-3	V
Gate Body Leakage	V <sub>GS</sub> = ±20V, V <sub>DS</sub> = 0V	I <sub>GSS</sub>	--	--	±100	nA
Zero Gate Voltage Drain Current	V <sub>DS</sub> = -30V, V <sub>GS</sub> = 0V	I <sub>DSS</sub>	--	--	-1.0	μA
On-State Drain Current <sup>a</sup>	V <sub>DS</sub> = -5V, V <sub>GS</sub> = -10V	I <sub>D(ON)</sub>	-50	--	--	A
Drain-Source On-State Resistance <sup>a</sup>	V <sub>GS</sub> = -10V, I <sub>D</sub> = -11A	R <sub>DS(ON)</sub>	--	10	12	mΩ
	V <sub>GS</sub> = -4.5V, I <sub>D</sub> = -8.5A		--	15	19	
Forward Transconductance <sup>a</sup>	V <sub>DS</sub> = -15V, I <sub>D</sub> = -11A	g <sub>fs</sub>	--	23	--	S
Diode Forward Voltage	I <sub>S</sub> = -2.1A, V <sub>GS</sub> = 0V	V <sub>SD</sub>	--	--	-1.3	V
<b>Dynamic<sup>b</sup></b>						
Total Gate Charge	V <sub>DS</sub> = -15V, I <sub>D</sub> = -11A, V <sub>GS</sub> = -10V	Q <sub>g</sub>	--	64	--	nC
Gate-Source Charge		Q <sub>gs</sub>	--	11	--	
Gate-Drain Charge		Q <sub>gd</sub>	--	25	--	
Input Capacitance	V <sub>DS</sub> = -8V, V <sub>GS</sub> = 0V, f = 1.0MHz	C <sub>iss</sub>	--	3680	--	pF
Output Capacitance		C <sub>oss</sub>	--	930	--	
Reverse Transfer Capacitance		C <sub>rss</sub>	--	620	--	
<b>Switching<sup>c</sup></b>						
Turn-On Delay Time	V <sub>DD</sub> = 15V, R <sub>L</sub> = 15Ω, I <sub>D</sub> = 1A, V <sub>GEN</sub> = -10V, R <sub>G</sub> = 6Ω	t <sub>d(on)</sub>	--	15	--	ns
Turn-On Rise Time		t <sub>r</sub>	--	13	--	
Turn-Off Delay Time		t <sub>d(off)</sub>	--	100	--	
Turn-Off Fall Time		t <sub>f</sub>	--	53	--	

**Notes:**

- a. pulse test: PW ≤ 300μs, duty cycle ≤ 2%
- b. For DESIGN AID ONLY, not subject to production testing.
- b. Switching time is essentially independent of operating temperature.




**Switching Test Circuit**




**Switchin Waveforms**

**Electrical Characteristics Curve**


**Output Characteristics**




**Transfer Characteristics**




**On-Resistance vs. Drain Current**




**Gate Charge**



**On-Resistance vs. Junction Temperature**




**Source-Drain Diode Forward Voltage**




**Electrical Characteristics Curve**


**On-Resistance vs. Gate-Source Voltage**




**Threshold Voltage**




**Single Pulse Power**




**Normalized Thermal Transient Impedance, Junction-to-Ambient**



**SOP-8 Mechanical Drawing**



**Marking Diagram**



Not Recommended

- Y = Year Code
- M = Month Code for Halogen Free Product
  - O =Jan    P =Feb    Q =Mar    R =Apr
  - S =May    T =Jun    U =Jul    V =Aug
  - W =Sep    X =Oct    Y =Nov    Z =Dec
- L = Lot Code



# TSM4425

## 30V P-Channel MOSFET

**Not Recommended**

### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View TSM4425CS RLG on WIN SOURCE](#)
- ⊖ [Taiwan Semiconductor](#) Information

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management