THE DATASHEET OF

BSP171PH6327XTSA1

www.win-source.net 0086-755-83957316

SIPMOS® Small-Signal-Transistor

Product Summary

V_{DS}	-60	V
$R_{DS(on),max}$	0.3	Ω
I_D	-1.9	A

Features

- P-Channel
- Enhancement mode
- Logic level
- Avalanche rated
- d*v*/d*t* rated
- Pb-free lead plating; RoHS compliant
- Qualified according to AEC Q101
- Halogen-free according to IEC61249-2-21

PG-SOT223



Type	Package	Tape and Reel Information	Marking	Packaging
BSP171P	PG-SOT223	H6327: 1000 pcs/reel	BSP171P	Non dry

Maximum ratings, at T_j=25 °C, unless otherwise specified

Parameter	Symbol	Conditions	Value	Unit
			steady state	
Continuous drain current	I_D	T_A=25 °C[1)]	-1.9	A
		T_A=70 °C[1)]	-1.5	
Pulsed drain current	$I_{D,pulse}$	T_A=25 °C	-7.6	
Avalanche energy, single pulse	E_{AS}	I_D=-1.9 A, R_{GS}=25 Ω	70	mJ
Reverse diode d*v*/d*t*	d*v*/d*t*	I_D=-1.9 A, V_{DS}=-48 V, d*i*/d*t*=-200 A/µs, $T_{j,max}$=150 °C	-6	kV/µs
Gate source voltage	V_{GS}		±20	V
Power dissipation	P_{tot}	T_A=25 °C[1)]	1.8	W
Operating and storage temperature	T_j, T_{stg}		-55 ... 150	°C
IEC climatic category; DIN IEC 68-1			55/150/56	
ESD Class; JESD22-A114-HBM			Class 1a	

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Thermal characteristics						
Thermal resistance, junction - soldering point	R_{thJS}		-	-	25	K/W
Thermal resistance, junction - ambient	R_{thJA}	minimal footprint, steady state	-	-	110	
		6 cm^2 cooling area[1)], steady state	-	-	70	
Electrical characteristics, at T_j=25 °C, unless otherwise specified						
Static characteristics						
Drain-source breakdown voltage	$V_{(BR)DSS}$	V_{GS}=0 V, I_D=-250 µA	-60	-	-	V
Gate threshold voltage	$V_{GS(th)}$	V_{DS}=V_{GS}, I_D=-460 µA	-1	-1.5	-2	
Zero gate voltage drain current	I_{DSS}	V_{DS}=-60 V, V_{GS}=0 V, T_j=25 °C	-	-0.1	-1	µA
		V_{DS}=-60 V, V_{GS}=0 V, T_j=125 °C	-	-10	-100	
Gate-source leakage current	I_{GSS}	V_{GS}=-20 V, V_{DS}=0 V	-	-10	-100	nA
Drain-source on-state resistance	$R_{DS(on)}$	V_{GS}=-4.5 V, I_D=-1.5 A	-	0.3	0.45	Ω
		V_{GS}=-10 V, I_D=-1.9 A	-	0.21	0.3	
Transconductance	g_{fs}	$\|V_{DS}\|>2\|I_D\|R_{DS(on)max}$, I_D=-1.5 A	1.4	2.7	-	S

[1)] Device on 40 mm x 40 mm x 1.5 mm epoxy PCB FR4 with 6 cm^2 (one layer, 70 µm thick) copper area for drain connection. PCB is vertical in still air.

Parameter	Symbol	Conditions	Values			Unit
			min.	typ.	max.	
Dynamic characteristics						
Input capacitance	C_{iss}	V_{GS}=0 V, V_{DS}=-25 V, f=1 MHz	-	365	460	pF
Output capacitance	C_{oss}		-	105	135	
Reverse transfer capacitance	C_{rss}		-	40	55	
Turn-on delay time	$t_{d(on)}$	V_{DD}=-25 V, V_{GS}=-10 V, I_D=-1.9 A, R_G=6 Ω	-	6	8	ns
Rise time	t_r		-	25	33	
Turn-off delay time	$t_{d(off)}$		-	208	276	
Fall time	t_f		-	87	130	
Gate Charge Characteristics[2)]						
Gate to source charge	Q_{gs}	V_{DD}=-48 V, I_D=1.9 A, V_{GS}=0 to -10 V	-	-1.2	-1.6	nC
Gate to drain charge	Q_{gd}		-	-5	-7	
Gate charge total	Q_g		-	-13	-20	
Gate plateau voltage	$V_{plateau}$		-	-3	-	V
Output charge	Q_{oss}	V_{DD}=-15 V, V_{GS}=0 V	-	-5	-7	
Reverse Diode						
Diode continuous forward current	I_S	T_A=25 °C	-	-	-1.9	A
Diode pulse current	$I_{S,pulse}$		-	-	-7.6	
Diode forward voltage	V_{SD}	V_{GS}=0 V, I_F=1.9 A, T_j=25 °C	-	-0.84	-1.1	V
Reverse recovery time	t_{rr}	V_R=-30 V, I_F=|I_S|, di_F/dt=100 A/µs	-	80	120	ns
Reverse recovery charge	Q_{rr}		-	-125	-190	nC

[2)] See figure 16 for gate charge parameter definition

1 Power dissipation

P_{tot}=f(T_A)



2 Drain current

I_D=f(T_A); |V_{GS}|≥10 V



3 Safe operating area

I_D=f(V_{DS}); T_A=25 °C[1]; D=0

parameter: t_p



4 Max. transient thermal impedance

Z_{thJA}=f(t_p)

parameter: D=t_p/T



5 Typ. output characteristics

I_D=f(V_{DS}); T_j=25 °C

parameter: V_{GS}



6 Typ. drain-source on resistance

$R_{DS(on)}$=f(I_D); T_j=25 °C

parameter: V_{GS}



7 Typ. transfer characteristics

I_D=f(V_{GS}); $|V_{DS}|>2|I_D|R_{DS(on)max}$

parameter: T_j



8 Typ. forward transconductance

g_{fs}=f(I_D); T_j=25 °C



9 Drain-source on-state resistance

$R_{DS(on)}$=f(T_j); I_D=-1.9 A; V_{GS}=-10 V



10 Typ. gate threshold voltage

$V_{GS(th)}$=f(T_j); V_{GS}=V_{DS}; I_D=-460 µA



11 Typ. capacitances

C=f(V_{DS}); V_{GS}=0 V; f=1 MHz



12 Forward characteristics of reverse diode

I_F=f(V_{SD})

parameter: T_j



13 Avalanche characteristics

I_{AS}=f(t_{AV}); R_{GS}=25 Ω

parameter: $T_{j(start)}$



14 Typ. gate charge

V_{GS}=f(Q_{gate}); I_D=-1.9 A pulsed

parameter: V_{DD}



15 Drain-source breakdown voltage

$V_{BR(DSS)}$=f(T_j); I_D=-1 mA



16 Gate charge waveforms



Package Outline

SOT-223: Outline



Footprint



Packaging

Tape



Dimensions in mm

Published by
Infineon Technologies AG
81726 Munich, Germany
© 2008 Infineon Technologies AG
All Rights Reserved.

Legal Disclaimer
The information given in this document shall in no event be regarded as a guarantee of conditions or characteristics. With respect to any examples or hints given herein, any typical values stated herein and/or any information regarding the application of the device, Infineon Technologies hereby disclaims any and all warranties and liabilities of any kind, including without limitation, warranties of non-infringement of intellectual property rights of any third party.

Information
For further information on technology, delivery terms and conditions and prices, please contact the nearest Infineon Technologies Office (www.infineon.com).

Warnings
Due to technical requirements, components may contain dangerous substances. For information on the types in question, please contact the nearest Infineon Technologies Office.
Infineon Technologies components may be used in life-support devices or systems only with the express written approval of Infineon Technologies, if a failure of such components can reasonably be expected to cause the failure of that life-support device or system or to affect the safety or effectiveness of that device or system. Life support devices or systems are intended to be implanted in the human body or to support and/or maintain and sustain and/or protect human life. If they fail, it is reasonable to assume that the health of the user or other persons may be endangered.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View BSP171PH6327XTSA1 on WIN SOURCE
- Infineon Technologies Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management