



**THE DATASHEET OF
AVO100B-48S3V3-6L**



ARTESYN AVO100 SERIES

100 Watts



Advanced Energy's Artesyn AVO100 series of eighth-brick isolated DC-DC converters comprises six single output models offering fully regulated voltages of 1.2 V, 1.5 V, 1.8 V, 2.5 V, 3.3 V or 5.0 V. These converters can deliver up to 50 amps and up to 100 watts of output power, depending on the particular model. They have a wide 2:1 input range of 36 to 75 Vdc and are designed primarily for use with standard 48 V telecommunications equipment supplies.

DATA SHEET

Total Power:

100 Watts

Input Voltage:

36 - 75 V

of Outputs:

Single

SPECIAL FEATURES

- 2:1 wide input range
- Optimised for high density, small space applications
- Low ripple and noise
- Fixed switching frequency
- High efficiency
- High capacitive load capability
- Basic insulation system
- Pre-bias start-up capability
- Open-frame structure
- Output overcurrent protection

SAFETY

- TUV/CE 62368-1
- UL/cUL 60950-1



ELECTRICAL SPECIFICATIONS

Input	
Input range	36 - 75 VDC
Efficiency ²	92.8% @ 5 V
Output	
Voltage tolerance	+/-1.5%
Line regulation	3.3 V: 0.3%; Others: 0.1%
Load regulation	3.3 V: 0.6%; 5 V: 0.2%; Others: 0.1%
Noise/ripple	3.3 Vo: 3.3V: 60 mV; 5V: 90 mV; 5.0 Vo: Others: 75 mV
Overvoltage protection Overtemperature protection	Auto-restart
Switching frequency	3.3 V, 5 V: 310 KHz; Others: 210 KHz
Temperature co-efficient	±0.02/°C
Isolation	
I/O isolation	5 V: 2250 VDC; Others: 1500V DC

ENVIRONMENTAL SPECIFICATIONS


Operating ambient temperature range	-40 °C to +85 °C
Storage temperature	-55 °C to +125 °C
Humidity	5% to 95% (non-condensing)
MTBF	2.5 Million hours
RoHS Compliant	

ORDERING INFORMATION

Model number	Input voltage	Output voltage	Power
AVO100-48S1V2-6L	36 - 75 Vin	1.2 V @ 50 A	60 W
AVO100-48S1V2B-6L	36 - 75 Vin	1.2 V @ 50 A	60 W
AVO100B-48S1V5-6L	36 - 75 Vin	1.5 V @ 40 A	60 W
AVO100B-48S1V5B-6L	36 - 75 Vin	1.5 V @ 40 A	60 W
AVO100B-48S1V5P-6L	36 - 75 Vin	1.5 V @ 40 A	60 W
AVO100B-48S1V5PB-6L	36 - 75 Vin	1.5 V @ 40 A	60 W
AVO100-48S1V8-6L	36 - 75 Vin	1.8 V @ 40 A	72 W
AVO100-48S1V8B-6L	36 - 75 Vin	1.8 V @ 40 A	72 W
AVO100-48S1V8P-6L	36 - 75 Vin	1.8 V @ 40 A	72 W
AVO100-48S1V8PB-6L	36 - 75 Vin	1.8 V @ 40 A	72 W
AVO100-48S2V5-6L	36 - 75 Vin	2.5 V @ 35 A	87.5 W
AVO100-48S2V5B-6L	36 - 75 Vin	2.5 V @ 35 A	87.5 W
AVO100-48S2V5P-6L	36 - 75 Vin	2.5 V @ 35 A	87.5 W
AVO100-48S2V5PB-6L	36 - 75 Vin	2.5 V @ 35 A	87.5 W
AVO100B-48S3V3-6L	36 - 75 Vin	3.3 V @ 30 A	99 W
AVO100B-48S3V3SL	36 - 75 Vin	3.3 V @ 30 A	99 W
AVO100C-48S3V3B-4L	36 - 75 Vin	3.3 V @ 30 A	99 W
AVO100C-48S3V3PB-4L	36 - 75 Vin	3.3 V @ 30 A	99 W
AVO100-48S05-6L	36 - 75 Vin	5 V @ 20 A	100 W
AVO100-48S05B-6L	36 - 75 Vin	5 V @ 20 A	100 W
AVO100-48S05P-6L	36 - 75 Vin	5 V @ 20 A	100 W
AVO100-48S05PB-6L	36 - 75 Vin	5 V @ 20 A	100 W
AVO100-48S05SL	36 - 75 Vin	5 V @ 20 A	100 W

- Standard version is negative enable
- "-6" = 3.8 mm pin length
- "-4" = 4.8 mm pin length
- "-P" = Positive enable
- "-S" = Surface mount, tray package
- "-L" = RoHS 6 compliance
- "-B" = Baseplate

MECHANICAL DRAWINGS



UNIT: mm[inch]

BOTTOM VIEW: pin on upside

TOLERANCE: X.Xmm±0.5mm[X.X in.±0.02in.]

X.XXmm±0.25mm[X.XX in.±0.01in.]

PIN DESIGNATIONS

Pin #	Function
1	+V in
2	Enable
3	-V in
4	-V out
5	-Sense
6	Trim
7	+Sense
8	+V out

Notes:

1. All specifications are subject to change without notice. Mechanical drawings are for reference only.
2. Warranty: 2 years
3. Label and logo appearance may vary from what is shown on mechanical drawings.



For international contact information,
visit advancedenergy.com.

powersales@aei.com (Sales Support)
productsupport.ep@aei.com (Technical Support)
+1 888 412 7832

ABOUT ADVANCED ENERGY

Advanced Energy (AE) has devoted more than three decades to perfecting power for its global customers. AE designs and manufactures highly engineered, precision power conversion, measurement and control solutions for mission-critical applications and processes.

Our products enable customer innovation in complex applications for a wide range of industries including semiconductor equipment, industrial, manufacturing, telecommunications, data center computing, and medical. With deep applications know-how and responsive service and support across the globe, we build collaborative partnerships to meet rapid technological developments, propel growth for our customers, and innovate the future of power.

PRECISION | POWER | PERFORMANCE

Specifications are subject to change without notice. Not responsible for errors or omissions. ©2020 Advanced Energy Industries, Inc. All rights reserved. Advanced Energy®, AE® and Artesyn™ are U.S. trademarks of Advanced Energy Industries, Inc.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- ⊖ [View AVO100B-48S3V3-6L on WIN SOURCE](#)
- ⊖ [Artesyn Embedded Technologies Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management