THE DATASHEET OF

NTMFD001N03P9

www.win-source.net 0086-755-83957316

MOSFET – Power, Dual, N-Channel, Power Clip, Trench, Asymmetric
30 V

NTMFD001N03P9

ON Semiconductor®

www.onsemi.com

Features
- Small Footprint (5x6 mm) for Compact Design
- Low $R_{DS(on)}$ to Minimize Conduction Losses
- Low Q_G and Capacitance to Minimize Driver Losses
- These Devices are Pb−Free, Halogen Free/BFR Free and are RoHS Compliant

Typical Applications
- DC−DC Converters
- System Voltage Rails

FET	$V_{(BR)DSS}$	$R_{DS(ON)}$ MAX	I_D MAX
Q1	30 V	5.0 mΩ @ 10 V	57 A
		6.5 mΩ @ 4.5 V	
Q2	30 V	1.0 mΩ @ 10 V	165 A
		1.2 mΩ @ 4.5 V	



PQFN8 POWER CLIP CASE 483AR

MARKING DIAGRAM



$Y = ON Semiconductor Logo
&Z = Assembly Plant Code
&3 = Numeric Date Code
&K = Lot Code
39HN = Specific Device Code

ELECTRICAL CONNECTION





ORDERING INFORMATION
See detailed ordering and shipping information on page 10 of this data sheet.

© Semiconductor Components Industries, LLC, 2018

Table 1. MAXIMUM RATINGS (T_J = 25°C unless otherwise stated)

Parameter			Symbol	Q1	Q2	Unit
Drain−to−Source Voltage			V_{DSS}	30	30	V
Gate−to−Source Voltage			V_{GS}	±20	+16 V −12 V	V
Continuous Drain Current $R_{\theta JC}$ (Note 3)	Steady State	T_C = 25°C	I_D	57	165	A
		T_C = 85°C		41	119	
Power Dissipation $R_{\theta JC}$ (Note 3)		T_C = 25°C	P_D	25	41	W
Continuous Drain Current $R_{\theta JA}$ (Note 1, 3)	Steady State	T_A = 25°C	I_D	16	38	A
		T_A = 85°C		12	27	
Power Dissipation $R_{\theta JA}$ (Note 1, 3)		T_A = 25°C	P_D	2.1	2.3	W
Continuous Drain Current $R_{\theta JA}$ (Note 2, 3)	Steady State	T_A = 25°C	I_D	11	25	A
		T_A = 85°C		8	18	
Power Dissipation $R_{\theta JA}$ (Note 2, 3)		T_A = 25°C	P_D	0.96	1.04	W
Pulsed Drain Current	T_A = 25°C, t_p = 10 μs		I_{DM}	300	500	A
Single Pulse Drain−to−Source Avalanche Energy Q1: I_L = 5.3 A_{pk}, L = 3 mH (Note 4) Q2: I_L = 8.35 A_{pk}, L = 3 mH (Note 4)			E_{AS}	42	104	mJ
Operating Junction and Storage Temperature			T_J, T_{stg}	−55 to 150		°C
Lead Temperature Soldering Reflow for Soldering Purposes (1/8″ from case for 10 s)			T_L	260		°C

Stresses exceeding those listed in the Maximum Ratings table may damage the device. If any of these limits are exceeded, device functionality should not be assumed, damage may occur and reliability may be affected.

Table 2. THERMAL RESISTANCE RATINGS

Parameter	Symbol	Q1 Max	Q2 Max	Units
Junction−to−Case − Steady State (Note 1, 3)	$R_{\theta JC}$	5.0	3.0	°C/W
Junction−to−Ambient − Steady State (Note 1, 3)	$R_{\theta JA}$	60	55	
Junction−to−Ambient − Steady State (Note 2, 3)	$R_{\theta JA}$	130	120	

1. Surface−mounted on FR4 board using 1 in^2 pad size, 2 oz Cu pad.
2. Surface−mounted on FR4 board using minimum pad size, 2 oz Cu pad.
3. The entire application environment impacts the thermal resistance values shown. They are not constants and are only valid for the particular conditions noted. Actual continuous current will be limited by thermal & electro−mechanical application board design. $R_{\Theta CA}$ is determined by the user's board design.
4. Q1 100% UIS tested at L = 0.1 mH, I_{AS} = 20 A.
   Q2 100% UIS tested at L = 0.1 mH, I_{AS} = 47 A.

Table 3. ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise stated)

Parameter	Symbol	Test Condition	FET	Min	Typ	Max	Unit
OFF CHARACTERISTICS							
Drain−to−Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 250 μA	Q1	30			V
		V_{GS} = 0 V, I_D = 1 mA	Q2	30			
Drain−to−Source Breakdown Voltage Temperature Coefficient	$V_{(BR)DSS}$ / T_J	I_D = 250 μA, ref to 25°C	Q1		15		mV/°C
		I_D = 50 mA, ref to 25°C	Q2		16		
Zero Gate Voltage Drain Current	I_{DSS}	V_{GS} = 0 V, V_{DS} = 24 V, T_J = 25°C	Q1			1	μA
			Q2			500	
Gate−to−Source Leakage Current	I_{GSS}	V_{DS} = 0 V, V_{GS} = 20 V	Q1			100	nA
		V_{DS} = 0 V, V_{GS} = 16 V	Q2			100	
ON CHARACTERISTICS (Note 5)							
Gate Threshold Voltage	$V_{GS(TH)}$	V_{GS} = V_{DS}, I_D = 250 μA	Q1	1.0		3.0	V
		V_{GS} = V_{DS}, I_D = 1 mA	Q2	1.0		3.0	
Threshold Temperature Coefficient	$V_{GS(TH)}$ / T_J	I_D = 250 μA, ref to 25°C	Q1		−5		mV/°C
		I_D = 50 mA, ref to 25°C	Q2		−3		
Drain−to−Source On Resistance	$R_{DS(on)}$	V_{GS} = 10 V, I_D = 17 A	Q1		4.5	5.0	mΩ
		V_{GS} = 4.5 V, I_D = 14 A			5.4	6.5	
		V_{GS} = 10 V, I_D = 40 A	Q2		0.75	1.0	
		V_{GS} = 4.5 V, I_D = 37 A			0.9	1.2	
Forward Transconductance	g_{FS}	V_{DS} = 5 V, I_D = 14 A	Q1		93		S
		V_{DS} = 5 V, I_D = 37 A	Q2		248		
Gate Resistance	R_G	T_A = 25°C	Q1		1		Ω
			Q2		1		
CHARGES & CAPACITANCES							
Input Capacitance	C_{ISS}	V_{GS} = 0 V, V_{DS} = 15 V, f = 1 MHz	Q1		1224		pF
			Q2		6575		
Output Capacitance	C_{OSS}		Q1		397		pF
			Q2		2086		
Reverse Capacitance	C_{RSS}		Q1		42		pF
			Q2		138		
Total Gate Charge	$Q_{G(TOT)}$	Q1: V_{GS} = 4.5 V, V_{DS} = 15 V, I_D = 14 A; Q2: V_{GS} = 4.5 V, V_{DS} = 15 V, I_D = 37 A	Q1		7.9		nC
			Q2		43		
Gate−to−Drain Charge	Q_{GD}		Q1		2.0		nC
			Q2		9.5		
Gate−to−Source Charge	Q_{GS}		Q1		3.1		nC
			Q2		15.8		
Total Gate Charge	$Q_{G(TOT)}$	V_{GS} = 10 V, V_{DS} = 15 V, I_D = 14 A	Q1		17		nC
		V_{GS} = 10 V, V_{DS} = 15 V, I_D = 37 A	Q2		93		

5. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%
6. Switching characteristics are independent of operating junction temperatures

Table 3. ELECTRICAL CHARACTERISTICS (T_J = 25°C unless otherwise stated)

Parameter	Symbol	Test Condition		FET	Min	Typ	Max	Unit
SWITCHING CHARACTERISTICS, VGS = 4.5 V (Note 6)								
Turn−On Delay Time	$t_{d(ON)}$	V_{GS} = 4.5 V Q1: I_D = 14 A, V_{DD} = 15 V, R_G = 6 Ω Q2: I_D = 37 A, V_{DD} = 15 V, R_G = 6 Ω		Q1		36		ns
				Q2		12.6		
Rise Time	$t_{r(ON)}$			Q1		30.7		ns
				Q2		21.5		
Turn−Off Delay Time	$t_{d(OFF)}$			Q1		64.7		ns
				Q2		17.5		
Fall Time	t_f			Q1		23.5		ns
				Q2		7.3		
SWITCHING CHARACTERISTICS, VGS = 10 V (Note 6)								
Turn−On Delay Time	$t_{d(ON)}$	V_{GS} = 10 V Q1: I_D = 17 A, V_{DD} = 15 V, R_G = 6 Ω Q2: I_D = 40 A, V_{DD} = 15 V, R_G = 6 Ω		Q1		8.0		ns
				Q2		8.6		
Rise Time	$t_{r(ON)}$			Q1		2.0		ns
				Q2		18.2		
Turn−Off Delay Time	$t_{d(OFF)}$			Q1		23.5		ns
				Q2		4.5		
Fall Time	t_f			Q1		2.0		ns
				Q2		4.5		
SOURCE−TO−DRAIN DIODE CHARACTERISTICS								
Forward Diode Voltage	V_{SD}	V_{GS} = 0 V, I_S = 14 A	T_J = 25°C	Q1		0.79	1.2	V
			T_J = 125°C			0.66		
		V_{GS} = 0 V, I_S = 37 A	T_J = 25°C	Q2		0.77	1.2	
			T_J = 125°C			0.63		
Reverse Recovery Time	t_{RR}	V_{GS} = 0 V Q1: I_S = 14 A, dI/dt = 100 A/μs Q2: I_S = 37 A, dI/dt = 240 A/μs		Q1		23		ns
				Q2		4.6		
Reverse Recovery Charge	Q_{RR}			Q1		8.0		nC
				Q2		68.3		

5. Pulse Test: pulse width ≤ 300 μs, duty cycle ≤ 2%
6. Switching characteristics are independent of operating junction temperatures

TYPICAL CHARACTERISTICS – Q1



Figure 1. On−Region Characteristics



Figure 2. Transfer Characteristics



Figure 3. On−Resistance vs. Gate−to−Source Voltage



Figure 4. On−Resistance vs. Drain Current and Gate Voltage



Figure 5. On−Resistance Variation with Temperature



Figure 6. Drain−to−Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS – Q1



Figure 7. Capacitance Variation



Figure 8. Gate−to−Source Voltage vs. Total Charge



Figure 9. Resistive Switching Time Variation vs. Gate Resistance



Figure 10. Diode Forward Voltage vs. Current



Figure 11. Maximum Rated Forward Biased Safe Operating Area



Figure 12. Maximum Drain Current vs. Time in Avalanche

TYPICAL CHARACTERISTICS – Q1



Figure 13. Thermal Response

TYPICAL CHARACTERISTICS – Q2



Figure 14. On−Region Characteristics



Figure 15. Transfer Characteristics



Figure 16. On−Resistance vs. Gate−to−Source Voltage



Figure 17. On−Resistance vs. Drain Current and Gate Voltage



Figure 18. On−Resistance Variation with Temperature



Figure 19. Drain−to−Source Leakage Current vs. Voltage

TYPICAL CHARACTERISTICS – Q2



Figure 20. Capacitance Variation



Figure 21. Gate−to−Source Voltage vs. Total Charge



Figure 22. Resistive Switching Time Variation vs. Gate Resistance



Figure 23. Diode Forward Voltage vs. Current



Figure 24. Maximum Rated Forward Biased Safe Operating Area



Figure 25. Maximum Drain Current vs. Time in Avalanche

TYPICAL CHARACTERISTICS – Q2



Figure 26. Transient Thermal Impedance

ORDERING INFORMATION

Device	Package	Shipping
NTMFD001N03P9	DFN8 (Pb−Free)	3000 / Tape & Reel



PQFN8 5.00x6.00x0.75, 1.27P
CASE 483AR
ISSUE D

DATE 06 NOV 2023











RECOMMENDED LAND PATTERN

*FOR ADDITIONAL INFORMATION ON OUR PB-FREE STRATEGY AND SOLDERING DETAILS, PLEASE DOWNLOAD THE ON SEMICONDUCTOR SOLDERING AND MOUNTING TECHNIQUES REFERENCE MANUAL, SOLDERRM/D.

NOTES: UNLESS OTHERWISE SPECIFIED

A) DOES NOT FULLY CONFORM TO JEDEC REGISTRATION, MO-229, DATED 11/2001.
B) ALL DIMENSIONS ARE IN MILLIMETERS.
C) DIMENSIONS DO NOT INCLUDE BURRS OR MOLD FLASH. MOLD FLASH OR BURRS DOES NOT EXCEED 0.10MM.
D) DIMENSIONING AND TOLERANCING PER ASME Y14.5M-1994.

DIM	MILLIMETERS		
	MIN.	NOM.	MAX.
A	0.70	0.75	0.80
A1	0.00	-	0.05
A3	0.20 REF		
b	0.51 BSC		
D	4.90	5.00	5.10
D2	3.05	3.15	3.25
D3	4.12	4.22	4.32
D4	3.80	3.90	4.00
E	5.90	6.00	6.10
E2	2.36	2.46	2.56
E3	0.81	0.91	1.01
E4	1.27	1.37	1.47
E5	0.59 REF		
e	1.27 BSC		
e/2	0.635 BSC		
e1	3.81 BSC		
k	0.52 REF		
L	0.38	0.48	0.58
L4	1.47	1.57	1.67
z	0.55 REF		
z1	0.39 REF		

DOCUMENT NUMBER:	**98AON13666G**	Electronic versions are uncontrolled except when accessed directly from the Document Repository. Printed versions are uncontrolled except when stamped "CONTROLLED COPY" in red.
DESCRIPTION:	**PQFN8 5.00x6.00x0.75, 1.27P**	**PAGE 1 OF 1**

onsemi and onsemi are trademarks of Semiconductor Components Industries, LLC dba **onsemi** or its subsidiaries in the United States and/or other countries. **onsemi** reserves the right to make changes without further notice to any products herein. **onsemi** makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. **onsemi** does not convey any license under its patent rights nor the rights of others.

onsemi, onsemi, and other names, marks, and brands are registered and/or common law trademarks of Semiconductor Components Industries, LLC dba "**onsemi**" or its affiliates and/or subsidiaries in the United States and/or other countries. **onsemi** owns the rights to a number of patents, trademarks, copyrights, trade secrets, and other intellectual property. A listing of **onsemi**'s product/patent coverage may be accessed at www.onsemi.com/site/pdf/Patent−Marking.pdf. **onsemi** reserves the right to make changes at any time to any products or information herein, without notice. The information herein is provided "as−is" and **onsemi** makes no warranty, representation or guarantee regarding the accuracy of the information, product features, availability, functionality, or suitability of its products for any particular purpose, nor does **onsemi** assume any liability arising out of the application or use of any product or circuit, and specifically disclaims any and all liability, including without limitation special, consequential or incidental damages. Buyer is responsible for its products and applications using **onsemi** products, including compliance with all laws, regulations and safety requirements or standards, regardless of any support or applications information provided by **onsemi**. "Typical" parameters which may be provided in **onsemi** data sheets and/or specifications can and do vary in different applications and actual performance may vary over time. All operating parameters, including "Typicals" must be validated for each customer application by customer's technical experts. **onsemi** does not convey any license under any of its intellectual property rights nor the rights of others. **onsemi** products are not designed, intended, or authorized for use as a critical component in life support systems or any FDA Class 3 medical devices or medical devices with a same or similar classification in a foreign jurisdiction or any devices intended for implantation in the human body. Should Buyer purchase or use **onsemi** products for any such unintended or unauthorized application, Buyer shall indemnify and hold **onsemi** and its officers, employees, subsidiaries, affiliates, and distributors harmless against all claims, costs, damages, and expenses, and reasonable attorney fees arising out of, directly or indirectly, any claim of personal injury or death associated with such unintended or unauthorized use, even if such claim alleges that **onsemi** was negligent regarding the design or manufacture of the part. **onsemi** is an Equal Opportunity/Affirmative Action Employer. This literature is subject to all applicable copyright laws and is not for resale in any manner.

ADDITIONAL INFORMATION

TECHNICAL PUBLICATIONS:
Technical Library: www.onsemi.com/design/resources/technical−documentation
onsemi Website: www.onsemi.com

ONLINE SUPPORT: www.onsemi.com/support
For additional information, please contact your local Sales Representative at
www.onsemi.com/support/sales

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View NTMFD001N03P9 on WIN SOURCE
- ON Semiconductor Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management