



**THE DATASHEET OF
GDZ7V5B-HG3-08**





Small Signal Zener Diodes



FEATURES

- Silicon planar Zener diodes
- Low Zener impedance and low leakage current
- Popular in Asian designs
- Compact surface mount device
- Ideal for automated mounting
- AEC-Q101 qualified available
- ESD capability according to AEC-Q101:
 - human body model > 8 kV
 - machine model > 800 V
- Base P/N-G3 - green, commercial grade
- Base P/N-HG3 - green, AEC-Q101 qualified
- Material categorization: for definitions of compliance please see www.vishay.com/doc?99912



DESIGN SUPPORT TOOLS

[click logo to get started](#)



| PRIMARY CHARACTERISTICS | | |
|------------------------------|---------------|------|
| PARAMETER | VALUE | UNIT |
| V _Z range nom. | 2.0 to 36 | V |
| Test current I _{ZT} | 5 | mA |
| V _Z specification | Pulse current | |
| Circuit configuration | Single | |

| ORDERING INFORMATION | | | |
|----------------------|---------------------------------|--------------------------------|------------------------|
| DEVICE NAME | ORDERING CODE | TAPED UNITS PER REEL | MINIMUM ORDER QUANTITY |
| GDZ-G-series | GDZ2V0B-G3-08 to GDZ36B-G3-08 | 3000 (8 mm tape on 7" reel) | 15 000/box |
| | GDZ2V0B-G3-18 to GDZ36B-G3-18 | 10 000 (8 mm tape on 13" reel) | 10 000/box |
| | GDZ2V0B-HG3-08 to GDZ36B-HG3-08 | 3000 (8 mm tape on 7" reel) | 15 000/box |
| | GDZ2V0B-HG3-18 to GDZ36B-HG3-18 | 10 000 (8 mm tape on 13" reel) | 10 000/box |

| PACKAGE | | | | |
|--------------|--------|--------------------------------------|-----------------------------------|--------------------------|
| PACKAGE NAME | WEIGHT | MOLDING COMPOUND FLAMMABILITY RATING | MOISTURE SENSITIVITY LEVEL | SOLDERING CONDITIONS |
| SOD-323 | 4 mg | UL 94 V-0 | MSL level 1 (according J-STD-020) | 260 °C/10 s at terminals |

| ABSOLUTE MAXIMUM RATINGS (T _{amb} = 25 °C, unless otherwise specified) | | | | |
|---|----------------|------------------|-------------|------|
| PARAMETER | TEST CONDITION | SYMBOL | VALUE | UNIT |
| Power dissipation | | P _{tot} | 200 | mW |
| Junction temperature | | T _j | 150 | °C |
| Storage temperature range | | T _{stg} | -55 to +150 | °C |
| Operating temperature range | | T _{op} | -55 to +150 | °C |



| ELECTRICAL CHARACTERISTICS (T _{amb} = 25 °C, unless otherwise specified) | | | | | | | | | |
|---|--------------|------------------------------------|-------|------------------|------------------|----------------------------------|-----|------------------------------------|-------------------------------------|
| PART NUMBER | MARKING CODE | ZENER VOLTAGE RANGE | | TEST CURRENT | | REVERSE CURRENT | | DYNAMIC RESISTANCE | |
| | | V _Z at I _{ZT1} | | I _{ZT1} | I _{ZT2} | I _R at V _R | | Z _Z at I _{ZT1} | Z _{ZK} at I _{ZT2} |
| | | V | | mA | | μA | V | Ω | |
| | | MIN. | MAX. | | | MAX. | | MAX. | MAX. |
| GDZ2V0B-G | 05 | 2.02 | 2.2 | 5 | 0.5 | 120 | 0.5 | 100 | 1000 |
| GDZ2V2B-G | 15 | 2.22 | 2.41 | 5 | 0.5 | 120 | 0.7 | 100 | 1000 |
| GDZ2V4B-G | 25 | 2.43 | 2.63 | 5 | 0.5 | 120 | 1 | 100 | 1000 |
| GDZ2V7B-G | 35 | 2.69 | 2.91 | 5 | 0.5 | 100 | 1 | 110 | 1000 |
| GDZ3V0B-G | 45 | 3.01 | 3.22 | 5 | 0.5 | 50 | 1 | 120 | 1000 |
| GDZ3V3B-G | 55 | 3.32 | 3.53 | 5 | 0.5 | 20 | 1 | 120 | 1000 |
| GDZ3V6B-G | 65 | 3.6 | 3.845 | 5 | 1 | 10 | 1 | 100 | 1000 |
| GDZ3V9B-G | 75 | 3.89 | 4.16 | 5 | 1 | 5 | 1 | 100 | 1000 |
| GDZ4V3B-G | 85 | 4.17 | 4.43 | 5 | 1 | 5 | 1 | 100 | 1000 |
| GDZ4V7B-G | 95 | 4.55 | 4.75 | 5 | 0.5 | 2 | 1 | 100 | 800 |
| GDZ5V1B-G | U1 | 4.98 | 5.2 | 5 | 0.5 | 2 | 1 | 80 | 500 |
| GDZ5V6B-G | U2 | 5.49 | 5.73 | 5 | 0.5 | 1 | 2.5 | 60 | 200 |
| GDZ6V2B-G | U3 | 6.06 | 6.33 | 5 | 0.5 | 1 | 3 | 60 | 100 |
| GDZ6V8B-G | U4 | 6.65 | 6.93 | 5 | 0.5 | 0.5 | 3.5 | 40 | 60 |
| GDZ7V5B-G | U5 | 7.28 | 7.6 | 5 | 0.5 | 0.5 | 4 | 30 | 60 |
| GDZ8V2B-G | U6 | 8.02 | 8.36 | 5 | 0.5 | 0.5 | 5 | 30 | 60 |
| GDZ9V1B-G | U7 | 8.85 | 9.23 | 5 | 0.5 | 0.5 | 6 | 30 | 60 |
| GDZ10B-G | U8 | 9.77 | 10.21 | 5 | 0.5 | 0.1 | 7 | 30 | 60 |
| GDZ11B-G | U9 | 10.76 | 11.22 | 5 | 0.5 | 0.1 | 8 | 30 | 60 |
| GDZ12B-G | UA | 11.74 | 12.24 | 5 | 0.5 | 0.1 | 9 | 30 | 80 |
| GDZ13B-G | UB | 12.91 | 13.49 | 5 | 0.5 | 0.1 | 10 | 37 | 80 |
| GDZ15B-G | UC | 14.34 | 14.98 | 5 | 0.5 | 0.1 | 11 | 42 | 80 |
| GDZ16B-G | UD | 15.85 | 16.51 | 5 | 0.5 | 0.1 | 12 | 50 | 80 |
| GDZ18B-G | UE | 17.56 | 18.35 | 5 | 0.5 | 0.1 | 13 | 65 | 80 |
| GDZ20B-G | UH | 19.52 | 20.39 | 5 | 0.5 | 0.1 | 15 | 85 | 100 |
| GDZ22B-G | UK | 21.54 | 22.47 | 5 | 0.5 | 0.1 | 17 | 100 | 100 |
| GDZ24B-G | UL | 23.72 | 24.78 | 5 | 0.5 | 0.1 | 19 | 120 | 120 |
| GDZ27B-G | UM | 26.19 | 27.53 | 5 | 0.5 | 0.1 | 21 | 150 | 150 |
| GDZ30B-G | UN | 29.19 | 30.69 | 5 | 0.5 | 0.1 | 23 | 200 | 200 |
| GDZ33B-G | UP | 32.15 | 33.79 | 5 | 0.5 | 0.1 | 25 | 250 | 250 |
| GDZ36B-G | UT | 35.07 | 36.87 | 5 | 0.5 | 0.1 | 27 | 300 | 300 |

Notes


- The Zener voltage V_Z is measured 40 ms after power is supplied
- The operating resistance (Z_Z, Z_{ZK}) are measured by superimposing a 1 kHz alternating current on the regulated current (I_Z).

TYPICAL CHARACTERISTICS ($T_{amb} = 25\text{ }^{\circ}\text{C}$, unless otherwise specified)



Fig. 1 - Zener Voltage Temperature Coefficient vs. Zener Voltage

PACKAGE DIMENSIONS in millimeters (inches): **SOD-323**



Footprint recommendation:

Document no.: S8-V-3910.02-001 (4)
 Created - Date: 24.August.2004
 Rev. 6 - Date: 23.Sept.2016
 17443



Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View GDZ7V5B-HG3-08 on WIN SOURCE](#)

 [Vishay Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management