



**THE DATASHEET OF
TDL 3-4822**



- Compact 3W Converter in DIP package
- I/O-isolation 1'500 VDC
- Fully regulated outputs
- Wide 2 : 1 input voltage range
- Operating temperature range -40°C to +80°C
- Short circuit protection
- 3-year product warranty



The TDL 3 series with 2:1 input voltage range is a selection of 3 Watt regulated dc/dc-converters. They come in a very compact DIP package (0.55 × 0.55 × 0.31 inch).

| Models | | | | |
|------------|--|----------------|---------------------|-----------------|
| Order code | Input voltage | Output voltage | Output current max. | Efficiency typ. |
| TDL 3-0510 | 4.5 – 10 VDC (5 VDC nominal) | 3.3 VDC | 600 mA | 79 % |
| TDL 3-0511 | | 5.0 VDC | 600 mA | 81 % |
| TDL 3-0512 | | 12 VDC | 250 mA | 85 % |
| TDL 3-0513 | | 15 VDC | 200 mA | 85 % |
| TDL 3-0521 | | ±5.0 VDC | ±300 mA | 82 % |
| TDL 3-0522 | | ±12 VDC | ±125 mA | 84 % |
| TDL 3-0523 | | ±15 VDC | ±100 mA | 85 % |
| TDL 3-1210 | 9 – 18 VDC (12 VDC nominal) | 3.3 VDC | 600 mA | 80 % |
| TDL 3-1211 | | 5.0 VDC | 600 mA | 83 % |
| TDL 3-1212 | | 12 VDC | 250 mA | 87 % |
| TDL 3-1213 | | 15 VDC | 200 mA | 87 % |
| TDL 3-1221 | | ±5.0 VDC | ±300 mA | 84 % |
| TDL 3-1222 | | ±12 VDC | ±125 mA | 86 % |
| TDL 3-1223 | | ±15 VDC | ±100 mA | 87 % |
| TDL 3-2410 | 18 – 36 VDC (24 VDC nominal) | 3.3 VDC | 600 mA | 80 % |
| TDL 3-2411 | | 5.0 VDC | 600 mA | 83 % |
| TDL 3-2412 | | 12 VDC | 250 mA | 87 % |
| TDL 3-2413 | | 15 VDC | 200 mA | 87 % |
| TDL 3-2421 | | ±5.0 VDC | ±300 mA | 84 % |
| TDL 3-2422 | | ±12 VDC | ±125 mA | 86 % |
| TDL 3-2423 | | ±15 VDC | ±100 mA | 87 % |
| TDL 3-4810 | 36 – 75 VDC (48 VDC nominal) | 3.3 VDC | 600 mA | 79 % |
| TDL 3-4811 | | 5.0 VDC | 600 mA | 82 % |
| TDL 3-4812 | | 12 VDC | 250 mA | 86 % |
| TDL 3-4813 | | 15 VDC | 200 mA | 86 % |
| TDL 3-4821 | | ±5.0 VDC | ±300 mA | 82 % |
| TDL 3-4822 | | ±12 VDC | ±125 mA | 85 % |
| TDL 3-4823 | | ±15 VDC | ±100 mA | 85 % |

Input Specifications

| | |
|--|--|
| Input current no load | 5 Vin models: 45 mA typ. 12 Vin models: 27 mA typ. 24 Vin models: 16 mA typ. 48 Vin models: 10 mA typ. |
| Surge voltage (1 sec. max.) | 5 Vin models: 12 V max. 12 Vin models: 25 V max. 24 Vin models: 50 V max. 48 Vin models: 100 V max. |
| Start-up voltage | 5 Vin models: 4.5 VDC max. 12 Vin models: 9.0 VDC max. 24 Vin models: 18 VDC max. 48 Vin models: 36 VDC max. |
| Input filter | internal capacitor |
| Conducted noise | EN 55022 class A or B (with ext. components) |
| ESD (electrostatic discharge) | EN 61000-4-2, air ± 8 kV, contact ± 6 kV, perf. criteria A |
| Radiated immunity | EN 61000-4-3, 10 V/m, perf. criteria A |
| Fast transient / surge (with external input capacitor) | EN 61000-4-4, ± 2 kV, perf. criteria A EN 61000-4-5, ± 1 kV perf. criteria A all models: Nippon chemi-con KY 220 μ F/100V -external input capacitor |
| Conducted immunity | EN 61000-4-6, 10 Vrms, perf. criteria A |
| Magnetic field immunity | EN 61000-4-8, 3 A/m, perf. criteria A |

Output Specifications

| | |
|--------------------------------------|---|
| Voltage set accuracy | ± 1.5 % max. |
| Voltage balance (dual output models) | 2 % max. |
| Regulation | - Input variation: 0.2 % max. - Load variation 0 – 100 %: 1 % max. dual output: 2 % max. (balanced load) cross regulation - dual output: 5 % max. (asymmetrical load 25 % / 100 %) |
| Minimum load | no minimum load required |
| Ripple and noise (20 MHz Bandwidth) | 70 mVp-p typ. |
| Transient response | - Recovery time (25% load step change): 500 μ s max. - Response deviation (25% load step change): 5 % max. |
| Short circuit protection | continuous, automatic recovery |
| Over load protection | at 170% of lout nom. (foldback) |
| Capacitive load | -Single output: all models: 100 μ F max. -Dual output: all models: 100 μ F max. (each output) |

General Specifications

| | |
|--------------------------------------|---|
| Temperature ranges | - Operating (convection cooling 20LFM, 0,1m/s): -40°C to +70°C (without derating) - Case temperature: +95°C max. - Storage temperature: -50°C to +125°C |
| Derating | 4.0%/K above 70°C |
| Humidity (non condensing) | 95 % rel H max. |
| Isolation voltage | - I/O isolation voltage (60 sec.): 1'500 VDC |
| Isolation capacitance (input/output) | 100 pF typ. |
| Isolation resistance (input/output) | >1 Gohm |
| Altitude during operation | 5'000 m |
| Temperature coefficient | ± 0.02 %/K max. |

All specifications valid at nominal input voltage, full load and +25°C after warm-up time unless otherwise stated.

General Specifications (continued)

| | |
|--|--|
| Reliability, calculated MTBF (MIL-HDBK-217F at +25°C, ground benign) | >3'450'000 h |
| Switching frequency | 100 kHz min. |
| Safety standards | UL 60950-1 IEC/EN 60950-1 www.tracopower.com/overview/tdl3 |
| Environmental compliance | – Reach – RoHS www.tracopower.com/products/reach-declaration.pdf RoHS directive 2011/65/EU |

Physical Specifications

| | |
|-----------------------|---|
| Casing material | non-conducting black plastic (UL 94V-0 rated) |
| Potting material | Epoxy (UL 94 V-0 rated) |
| Pin material | tinned copper |
| Package weight | 3.9 g (0.137 oz) |
| Soldering temperature | max. 260°C / 10 sec. |

Outline Dimensions



| Pin-Out | | |
|---------|------------|------------|
| Pin | Single | Dual |
| 1 | -Vin (GND) | -Vin (GND) |
| 4 | +Vin (Vcc) | +Vin (Vcc) |
| 5 | +Vout | +Vout |
| 6 | no pin | Common |
| 7 | -Vout | -Vout |





Dimensions in [mm], () = Inch
Tolerances: x.x ±0.5 (±0.02)
x.xx ±0.25 (±0.01)
pin dimension tolerance ±0.05 (±0.002)

Specifications can be changed without notice! Make sure you are using the latest documentation, downloadable at www.tracopower.com

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

-  [View TDL 3-4822 on WIN SOURCE](#)
-  [Traco Power Information](#)

Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management