





**THE DATASHEET OF  
EL816(S1)(TA)-V**



### 4 PIN DIP PHOTOTRANSISTOR PHOTOCOUPLER EL816 Series



Schematic



Pin Configuration

1. Anode
2. Cathode
3. Emitter
4. Collector

#### Features:

- Compliance Halogens Free (Only copper leadframe)  
(Br < 900 ppm, Cl < 900 ppm, Br+Cl < 1500 ppm)
- Current transfer ratio  
(CTR: 50~600% at  $I_F = 5\text{mA}$ ,  $V_{CE} = 5\text{V}$ )  
(CTR: 63~320% at  $I_F = 10\text{mA}$ ,  $V_{CE} = 5\text{V}$ )
- High isolation voltage between input and output (Viso=5000Vrms)
- Creepage distance > 7.62mm
- Operating temperature up to +110°C
- Compact small outline package
- The product itself will remain within RoHS compliant version
- Compliance with EU REACH
- UL and cUL approved(No. E214129)
- VDE approved (No. 132249)
- SEMKO approved
- NEMKO approved
- DEMKO approved
- FIMKO approved
- CQC approved

#### Description

The EL816 series of devices each consist of an infrared emitting diodes, optically coupled to a phototransistor detector. They are packaged in a 4-pin DIP package and available in wide-lead spacing and SMD option.

#### Applications

- Programmable controllers
- System appliances, measuring instruments
- Telecommunication equipments
- Home appliances, such as fan heaters, etc.
- Signal transmission between circuits of different potentials and impedances

**Absolute Maximum Ratings (Ta=25°C)**

|                         | Parameter   | Symbol     | Rating     | Unit        |
|-------------------------|---|------------|------------|-------------|
| Input                   | Forward current   | $I_F$      | 60         | mA          |
|                         | Peak forward current (1us, pulse)   | $I_{FP}$   | 1          | A           |
|                         | Reverse voltage   | $V_R$      | 6          | V           |
|                         | Power Dissipation<br>No derating required up to $T_a = 100^\circ\text{C}$ | $P_D$      | 100        | mW          |
| Output                  | Power dissipation<br>Derating factor (above $T_a = 80^\circ\text{C}$ )    | $P_C$      | 150<br>5.8 | mW<br>mW/°C |
|                         | Collector current   | $I_C$      | 50         | mA          |
|                         | Collector-Emitter voltage   | $V_{CEO}$  | 80         | V           |
|                         | Emitter-Collector voltage   | $V_{ECO}$  | 6          | V           |
|                         | Total Power Dissipation   | $P_{TOT}$  | 200        | mW          |
| Isolation Voltage*1     | $V_{ISO}$   | 5000       | Vrms       |             |
| Operating Temperature   | $T_{OPR}$   | -55 to 110 | °C         |             |
| Storage Temperature     | $T_{STG}$   | -55 to 125 | °C         |             |
| Soldering Temperature*2 | $T_{SOL}$   | 260        | °C         |             |

Notes:

\*1 AC for 1 minute, R.H.= 40 ~ 60% R.H. In this test, pins 1, 2 are shorted together, and pins 3, 4 are shorted together.

\*2 For 10 seconds

**Electro-Optical Characteristics (Ta=25°C unless specified otherwise)**

**Input**

| Parameter         | Symbol   | Min. | Typ. | Max. | Unit          | Condition                |
|-------------------|----------|------|------|------|---------------|--------------------------|
| Forward Voltage   | $V_F$    | -    | 1.2  | 1.4  | V             | $I_F = 20\text{mA}$      |
| Reverse Current   | $I_R$    | -    | -    | 10   | $\mu\text{A}$ | $V_R = 4\text{V}$        |
| Input capacitance | $C_{in}$ | -    | 30   | 250  | pF            | $V = 0, f = 1\text{kHz}$ |

**Output**

| Parameter                           | Symbol     | Min | Typ. | Max. | Unit | Condition                               |
|-------------------------------------|------------|-----|------|------|------|---|
| Collector-Emitter dark current      | $I_{CEO}$  | -   | -    | 100  | nA   | $V_{CE} = 20\text{V}, I_F = 0\text{mA}$ |
| Collector-Emitter breakdown voltage | $BV_{CEO}$ | 80  | -    | -    | V    | $I_C = 0.1\text{mA}$                    |
| Emitter-Collector breakdown voltage | $BV_{ECO}$ | 6   | -    | -    | V    | $I_E = 0.1\text{mA}$                    |

**Transfer Characteristics**

| Parameter              | Symbol | Min | Typ. | Max. | Unit | Condition                              |   |  |
|------------------------|--------|-----|------|------|------|--|---|--|
| Current Transfer ratio | EL816  | 50  | -    | 600  | %    | $I_F = 5\text{mA}, V_{CE} = 5\text{V}$ |   |  |
|                        | EL816A | 80  | -    | 160  |      |  |   |  |
|                        | EL816B | 130 | -    | 260  |      |  |   |  |
|                        | EL816C | 200 | -    | 400  |      |  |   |  |
|                        | EL816D | 300 | -    | 600  |      |  |   |  |
|                        | EL816X | 100 | -    | 200  |      |  |   |  |
|                        | EL816Y | 150 | -    | 300  |      |  |   |  |
|                        | EL816I | 63  | -    | 125  |      |  | $I_F = 10\text{mA}, V_{CE} = 5\text{V}$ |  |
|                        | EL816J | 100 | -    | 200  |      |  |   |  |
|                        | EL816K | 160 | -    | 320  |      |  |   |  |
|                        | EL816I | 22  | -    | -    |      |  |   |  |
|                        | EL816J | 34  | -    | -    |      |  |   | $I_F = 1\text{mA}, V_{CE} = 5\text{V}$ |
|                        | EL816K | 56  | -    | -    |      |  |   |  |

**Transfer Characteristics ( $T_a=25^\circ\text{C}$  unless specified otherwise) Continuity**

| Parameter                            | Symbol        | Min                | Typ. | Max. | Unit          | Condition  |
|--------------------------------------|---------------|--------------------|------|------|---------------|--|
| Collector-Emitter saturation voltage | $V_{CE(sat)}$ | -                  | 0.1  | 0.2  | V             | $I_F = 20\text{mA}, I_C = 1\text{mA}$                                    |
| Isolation resistance                 | $R_{IO}$      | $5 \times 10^{10}$ | -    | -    | $\Omega$      | $V_{IO} = 500\text{Vdc}$ ,<br>40~60% R.H.                                |
| Floating capacitance                 | $C_{IO}$      | -                  | 0.6  | 1.0  | pF            | $V_{IO} = 0, f = 1\text{MHz}$  |
| Cut-off frequency                    | $f_c$         | -                  | 80   | -    | kHz           | $V_{CE} = 5\text{V}, I_C = 2\text{mA}$<br>$R_L = 100\Omega, -3\text{dB}$ |
| Rise time                            | $t_r$         | -                  | 4    | 18   | $\mu\text{s}$ | $V_{CE} = 2\text{V}, I_C = 2\text{mA}$ ,<br>$R_L = 100\Omega$            |
| Fall time                            | $t_f$         | -                  | 3    | 18   | $\mu\text{s}$ |  |

\* Typical values at  $T_a = 25^\circ\text{C}$

EVERLIGHT

Typical Electro-Optical Characteristics Curves









Figure 7. Collector Dark Current vs Ambient Temperature




Figure 8. Switching Time vs Load Resistance




Figure 9. Collector-Emitter Saturation Voltage vs Ambient Temperature






Figure 10. Switching Time Test Circuit & Waveforms

**Order Information**

**Part Number**

**EL816X(Y)(Z)-FV**


**Note**

- X = Lead form option (S1, S2, M or none)
- Y = CTR Rank (A, B, C, D, X, Y, I, J, K or none)
- Z = Tape and reel option (TU, TD or none).
- F = Lead frame option (F: Iron, None: copper)
- V = VDE safety (optional).


| Option  | Description   | Packing quantity    |
|---------|---|---------------------|
| None    | Standard DIP-4  | 100 units per tube  |
| M       | Wide lead bend (0.4 inch spacing)                             | 100 units per tube  |
| S1 (TU) | Surface mount lead form (low profile) + TU tape & reel option | 1500 units per reel |
| S1 (TD) | Surface mount lead form (low profile) + TD tape & reel option | 1500 units per reel |
| S2 (TU) | Surface mount lead form (low profile) + TU tape & reel option | 2000 units per reel |
| S2 (TD) | Surface mount lead form (low profile) + TD tape & reel option | 2000 units per reel |

Package Dimension (Dimensions in mm)


Standard DIP Type




Option M Type



Option S1 Type




Option S2 Type




Recommended pad layout for surface mount leadform


For S1 option



For S2 option




Device Marking




Notes

- EL denotes EVERLIGHT
- 816 denotes Device Number
- R denotes CTR Rank(A, B, C, D, X, Y, I, J, K or none)
- Y denotes 1 digit Year code
- WW denotes 2 digit Week code
- V denotes VDE (optional)

Tape & Reel Packing Specifications



Tape dimensions




|                      |           |           |           |           |           |           |
|----------------------|-----------|-----------|-----------|-----------|-----------|-----------|
| Dimension No.        | <b>Ao</b> | <b>Bo</b> | <b>Do</b> | <b>D1</b> | <b>E</b>  | <b>F</b>  |
| Dimension (mm)<br>S1 | 4.90±0.1  | 10.40±0.1 | 1.5±0.1   | 1.50±0.1  | 1.75±0.1  | 7.50±0.1  |
| Dimension (mm)<br>S2 | 4.88±0.1  | 12.55±0.1 | 1.5±0.1   | 1.50±0.1  | 1.75±0.1  | 11.5±0.1  |
| Dimension No.        | <b>Po</b> | <b>P1</b> | <b>P2</b> | <b>t</b>  | <b>W</b>  | <b>Ko</b> |
| Dimension (mm)<br>S1 | 4.00±0.1  | 8.00±0.   | 2.00±0.1  | 0.40±0.1  | 16.00±0.3 | 4.60±0.1  |
| Dimension (mm)<br>S2 | 4.00±0.1  | 8.00±0.1  | 2.00±0.1  | 0.40±0.1  | 24.00±0.3 | 4.00±0.1  |

## Precautions for Use

### 1. Soldering Condition

#### 1.1 (A) Maximum Body Case Temperature Profile for evaluation of Reflow Profile



Note:

Reference: IPC/JEDEC J-STD-020D

#### Preheat

|  |                 |
|--|-----------------|
| Temperature min ( $T_{smin}$ )               | 150 °C          |
| Temperature max ( $T_{smax}$ )               | 200°C           |
| Time ( $T_{smin}$ to $T_{smax}$ ) ( $t_s$ )  | 60-120 seconds  |
| Average ramp-up rate ( $T_{smax}$ to $T_p$ ) | 3 °C/second max |

#### Other

|  |                  |
|--|------------------|
| Liquidus Temperature ( $T_L$ )                                       | 217 °C           |
| Time above Liquidus Temperature ( $t_L$ )                            | 60-100 sec       |
| Peak Temperature ( $T_P$ )   | 260°C            |
| Time within 5 °C of Actual Peak Temperature: $T_P - 5^\circ\text{C}$ | 30 s             |
| Ramp- Down Rate from Peak Temperature                                | 6°C /second max. |
| Time 25°C to peak temperature  | 8 minutes max.   |
| Reflow times   | 3 times          |

## DISCLAIMER

1. Above specification may be changed without notice. EVERLIGHT will reserve authority on material change for above specification.
2. The graphs shown in this datasheet are representing typical data only and do not show guaranteed values.
3. When using this product, please observe the absolute maximum ratings and the instructions for use outlined in these specification sheets. EVERLIGHT assumes no responsibility for any damage resulting from use of the product which does not comply with the absolute maximum ratings and the instructions included in these specification sheets.
4. These specification sheets include materials protected under copyright of EVERLIGHT. Reproduction in any form is prohibited without the specific consent of EVERLIGHT.
5. This product is not intended to be used for military, aircraft, automotive, medical, life sustaining or life saving applications or any other application which can result in human injury or death. Please contact authorized Everlight sales agent for special application request.
6. Statements regarding the suitability of products for certain types of applications are based on Everlight's knowledge of typical requirements that are often placed on Everlight products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and/or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Everlight's terms and conditions of purchase, including but not limited to the warranty expressed therein.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- [View EL816\(S1\)\(TA\)-V on WIN SOURCE](#)
- [Everlight Electronics Co Ltd Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

- ✓ Global Sourcing Solution
- ✓ Obsolete Management
- ✓ Cost Control Management
- ✓ Shortage Management
- ✓ Alternative Solution
- ✓ Excess Inventory Management