




**THE DATASHEET OF  
TCMT1116**






# Optocoupler, Phototransistor Output, Single Channel, Half Pitch Mini-Flat Package



22628-1



### FEATURES

- Low profile package (half pitch)
- AC isolation test voltage 3750 V<sub>RMS</sub>
- Low coupling capacitance of typical 0.3 pF
- Current transfer ratio (CTR) selected into groups
- Low temperature coefficient of CTR
- Wide ambient temperature range
- Material categorization: for definitions of compliance please see [www.vishay.com/doc?99912](http://www.vishay.com/doc?99912)



RoHS  
COMPLIANT

### DESCRIPTION

The TCMT111X series consist of a phototransistor optically coupled to a gallium arsenide infrared-emitting diode in a 4 pin package.


### APPLICATIONS

- Programmable logic controllers
- Modems
- Answering machines
- General applications

### AGENCY APPROVALS

- UL1577, file no. E76222, double protection
- cUL component acceptance service no. 5A, double protection
- DIN EN 60747-5-5 (VDE 0884-5)
- FIMKO: FI EN 60950-1:2006
- BSI: BS EN60065:2002  
BS EN60950-1:2006
- CQC GB 8898-2011, GB 4943.1-2011 (suitable for installation altitude below 2000 m)

| ORDERING INFORMATION  |           |            |            |           |            |            |
|---|-----------|------------|------------|-----------|------------|------------|
| <div style="display: flex; justify-content: space-around; align-items: center;"> <div style="border: 1px solid black; padding: 2px 5px;">T</div> <div style="border: 1px solid black; padding: 2px 5px;">C</div> <div style="border: 1px solid black; padding: 2px 5px;">M</div> <div style="border: 1px solid black; padding: 2px 5px;">T</div> <div style="border: 1px solid black; padding: 2px 5px;">1</div> <div style="border: 1px solid black; padding: 2px 5px;">1</div> <div style="border: 1px solid black; padding: 2px 5px;">1</div> <div style="border: 1px solid black; padding: 2px 5px;">#</div> </div> <p style="text-align: center; margin-top: 5px;">PART NUMBER</p> |           |            |            |           |            |            |
| AGENCY CERTIFIED/PACKAGE  | CTR (%)   |            |            |           |            |            |
|   | 5 mA      | 10 mA      | 5 mA       |           |            |            |
| UL, cUL, BSI, VDE   | 50 to 600 | 100 to 200 | 100 to 300 | 80 to 160 | 130 to 260 | 200 to 400 |
| SSOP-4  | TCMT1110  | TCMT1113   | TCMT1116   | TCMT1117  | TCMT1118   | TCMT1119   |



| ABSOLUTE MAXIMUM RATINGS (T <sub>amb</sub> = 25 °C, unless otherwise specified) |                        |                   |       |      |
|---|------------------------|-------------------|-------|------|
| PARAMETER   | TEST CONDITION         | SYMBOL            | VALUE | UNIT |
| <b>INPUT</b>  |                        |                   |       |      |
| Reverse voltage   |                        | V <sub>R</sub>    | 6     | V    |
| Forward current   |                        | I <sub>F</sub>    | 50    | mA   |
| Forward surge current   | t <sub>p</sub> ≤ 10 μs | I <sub>FSM</sub>  | 1.5   | A    |
| Power dissipation   |                        | P <sub>diss</sub> | 80    | mW   |
| Junction temperature  |                        | T <sub>j</sub>    | 125   | °C   |



| ABSOLUTE MAXIMUM RATINGS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |                                      |            |             |                    |
|---|--------------------------------------|------------|-------------|--------------------|
| PARAMETER   | TEST CONDITION                       | SYMBOL     | VALUE       | UNIT               |
| <b>OUTPUT</b>   |                                      |            |             |                    |
| Collector emitter voltage   |                                      | $V_{CEO}$  | 70          | V                  |
| Emitter collector voltage   |                                      | $V_{ECO}$  | 7           | V                  |
| Collector current   |                                      | $I_C$      | 50          | mA                 |
| Collector peak current  | $t_p/T = 0.5, t_p \leq 10\text{ ms}$ | $I_{CM}$   | 100         | mA                 |
| Power dissipation   |                                      | $P_{diss}$ | 150         | mW                 |
| Junction temperature  |                                      | $T_j$      | 125         | $^{\circ}\text{C}$ |
| <b>COUPLER</b>  |                                      |            |             |                    |
| Total power dissipation   |                                      | $P_{tot}$  | 230         | mW                 |
| Operating ambient temperature range   |                                      | $T_{amb}$  | -40 to +110 | $^{\circ}\text{C}$ |
| Storage temperature range   |                                      | $T_{stg}$  | -40 to +125 | $^{\circ}\text{C}$ |
| Soldering temperature <sup>(1)</sup>  |                                      | $T_{sld}$  | 260         | $^{\circ}\text{C}$ |

**Notes**

- Stresses in excess of the absolute maximum ratings can cause permanent damage to the device. Functional operation of the device is not implied at these or any other conditions in excess of those given in the operational sections of this document. Exposure to absolute maximum ratings for extended periods of the time can adversely affect reliability.

<sup>(1)</sup> Wave soldering three cycles are allowed. Also refer to "Assembly Instructions" ([www.vishay.com/doc?80054](http://www.vishay.com/doc?80054)).


| ELECTRICAL CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |  |             |      |      |      |      |
|---|--|-------------|------|------|------|------|
| PARAMETER   | TEST CONDITION   | SYMBOL      | MIN. | TYP. | MAX. | UNIT |
| <b>INPUT</b>  |  |             |      |      |      |      |
| Forward voltage   | $I_F = 5\text{ mA}$  | $V_F$       | -    | 1.08 | 1.4  | V    |
| Junction capacitance  | $V_R = 0, f = 1\text{ MHz}$  | $C_j$       | -    | 8    | -    | pF   |
| <b>OUTPUT</b>   |  |             |      |      |      |      |
| Collector emitter voltage   | $I_C = 100\text{ }\mu\text{A}$                                     | $V_{CEO}$   | 70   | -    | -    | V    |
| Emitter collector voltage   | $I_E = 100\text{ }\mu\text{A}$                                     | $V_{ECO}$   | 7    | -    | -    | V    |
| Collector dark current  | $V_{CE} = 20\text{ V}, I_F = 0$                                    | $I_{CEO}$   | -    | -    | 100  | nA   |
| <b>COUPLER</b>  |  |             |      |      |      |      |
| Collector emitter saturation voltage  | $I_F = 10\text{ mA}, I_C = 1\text{ mA}$                            | $V_{CEsat}$ | -    | 0.1  | 0.3  | V    |
| Cut-off frequency   | $V_{CE} = 5\text{ V}, I_F = 10\text{ mA}, R_L = 100\text{ }\Omega$ | $f_c$       | -    | 100  | -    | kHz  |
| Coupling capacitance  | $f = 1\text{ MHz}$   | $C_k$       | -    | 0.3  | -    | pF   |

**Note**

- Minimum and maximum values are testing requirements. Typical values are characteristics of the device and are the result of engineering evaluation. Typical values are for information only and are not part of the testing requirements.

| CURRENT TRANSFER RATIO ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |   |          |        |      |      |      |      |
|---|---|----------|--------|------|------|------|------|
| PARAMETER   | TEST CONDITION                            | PART     | SYMBOL | MIN. | TYP. | MAX. | UNIT |
| $I_C/I_F$   | $V_{CE} = 5\text{ V}, I_F = 5\text{ mA}$  | TCMT1110 | CTR    | 50   | -    | 600  | %    |
|   | $V_{CE} = 5\text{ V}, I_F = 10\text{ mA}$ | TCMT1113 | CTR    | 100  | -    | 200  | %    |
|   |   | TCMT1114 | CTR    | 160  | -    | 320  | %    |
|   | $V_{CE} = 5\text{ V}, I_F = 5\text{ mA}$  | TCMT1117 | CTR    | 80   | -    | 160  | %    |
|   |   | TCMT1118 | CTR    | 130  | -    | 260  | %    |
|   |   | TCMT1119 | CTR    | 200  | -    | 400  | %    |

| SWITCHING CHARACTERISTICS ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified) |   |           |      |      |      |               |
|--|---|-----------|------|------|------|---------------|
| PARAMETER  | TEST CONDITION  | SYMBOL    | MIN. | TYP. | MAX. | UNIT          |
| Delay time   | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_d$     | -    | 4    | -    | $\mu\text{s}$ |
| Rise time  | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_r$     | -    | 5.5  | -    | $\mu\text{s}$ |
| Fall time  | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_f$     | -    | 7    | -    | $\mu\text{s}$ |
| Storage time   | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_s$     | -    | 1.5  | -    | $\mu\text{s}$ |
| Turn-on time   | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_{on}$  | -    | 9.5  | -    | $\mu\text{s}$ |
| Turn-off time  | $V_S = 5\text{ V}$ , $I_C = 2\text{ mA}$ , $R_L = 100\text{ }\Omega$ , (see figure 1) | $t_{off}$ | -    | 8    | -    | $\mu\text{s}$ |
| Turn-on time   | $V_S = 5\text{ V}$ , $I_F = 10\text{ mA}$ , $R_L = 1\text{ k}\Omega$ , (see figure 2) | $t_{on}$  | -    | 3    | -    | $\mu\text{s}$ |
| Turn-off time  | $V_S = 5\text{ V}$ , $I_F = 10\text{ mA}$ , $R_L = 1\text{ k}\Omega$ , (see figure 2) | $t_{off}$ | -    | 20   | -    | $\mu\text{s}$ |



95 10804

Fig. 1 - Test Circuit, Non-Saturated Operation





Fig. 3 - Switching Times



95 10843

Fig. 2 - Test Circuit, Saturated Operation

| SAFETY AND INSULATION RATINGS                                |  |            |            |                    |
|--|--|------------|------------|--------------------|
| PARAMETER  | TEST CONDITION   | SYMBOL     | VALUE      | UNIT               |
| Climatic classification (according to IEC 68 part 1)         |  |            | 55/110/21  |                    |
| Comparative tracking index                                   |  | CTI        | 175        |                    |
| Maximum rated withstanding isolation voltage                 | 40 % to 60 % RH, AC test of 1 min  | $V_{ISO}$  | 3750       | $V_{RMS}$          |
| Maximum transient isolation voltage                          |  | $V_{IOTM}$ | 6000       | V                  |
| Maximum repetitive peak isolation voltage                    |  | $V_{IORM}$ | 707        | V                  |
| Insulation resistance  | $V_{IO} = 500\text{ V}$ , $T_{amb} = 100\text{ }^{\circ}\text{C}$  | $R_{IO}$   | $10^{11}$  | $\Omega$           |
| Isolation resistance (under fault conditions)                | $V_{IO} = 500\text{ V}$ , $T_{amb} = T_{SI}$   | $R_{IO}$   | $10^9$     | $\Omega$           |
| Output safety power  |  | $P_{SO}$   | 350        | mW                 |
| Input safety current   |  | $I_{SI}$   | 200        | mA                 |
| Input safety temperature                                     |  | $T_{SI}$   | 175        | $^{\circ}\text{C}$ |
| Apparent charge test voltage (method A)                      | $V_{IORM} \times 1.6 = V_{PR}$ , type and sample test<br>$t_m = 60\text{ s}$ , partial discharge < 5 pC        | $V_{PR}$   | 1132       | $V_{peak}$         |
| Apparent charge test voltage (method B)                      | $V_{IORM} \times 1.875 = V_{PR}$ , 100 % production<br>test with $t_m = 1\text{ s}$ , partial discharge < 5 pC | $V_{PR}$   | 1326       | $V_{peak}$         |
| Creepage distance  |  |            | $\geq 5$   | mm                 |
| Clearance distance   |  |            | $\geq 5$   | mm                 |
| Insulation thickness   |  | DTI        | $\geq 0.4$ | mm                 |
| Environment (pollution degree in accordance to DIN VDE 0109) |  |            | 2          |                    |

**Note**

- As per IEC 60747-5-5, § 7.4.3.8.2, this optocoupler is suitable for “safe electrical insulation” only within the safety ratings. Compliance with the safety ratings shall be ensured by means of protective circuits.

**TYPICAL CHARACTERISTICS** ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)




Fig. 4 - Total Power Dissipation vs. Ambient Temperature




Fig. 5 - Forward Voltage vs. Forward Current




Fig. 6 - Collector Current vs. Collector Emitter Voltage




Fig. 9 - Normalized Current Transfer Ratio (non-saturated) vs. Ambient Temperature




Fig. 7 - Leakage Current vs. Ambient Temperature




Fig. 10 - Normalized Current Transfer Ratio (saturated) vs. Ambient Temperature




Fig. 8 - Collector Current vs. Collector Emitter Voltage




Fig. 11 - Collector Emitter Voltage vs. Ambient Temperature




Fig. 12 - Normalized CTR (non-saturated) vs. Forward Current




Fig. 15 -  $F_{CTR}$  vs. Collector Current




Fig. 13 - Normalized CTR (saturated) vs. Forward Current




Fig. 16 - Switching Time vs. Load Resistance






Fig. 14 -  $F_{CTR}$  vs. Phase Angle



## PACKAGE DIMENSIONS in millimeters



## PACKAGE MARKING (example of TCMT1110)



**PACKAGING INFORMATION (TAPE AND REEL) in millimeters**





Fig. 17 - Tape and Reel Shipping Medium



**SOLDER PROFILES**




Fig. 19 - Lead (Pb)-free Reflow Solder Profile According to J-STD-020 for SMD Devices

**HANDLING AND STORAGE CONDITIONS**

ESD level: HBM class 2  
 Floor life: unlimited  
 Conditions:  $T_{amb} < 30\text{ °C}$ ,  $RH < 85\%$   
 Moisture sensitivity level 1, according to J-STD-020



## Disclaimer

ALL PRODUCT, PRODUCT SPECIFICATIONS AND DATA ARE SUBJECT TO CHANGE WITHOUT NOTICE TO IMPROVE RELIABILITY, FUNCTION OR DESIGN OR OTHERWISE.

Vishay Intertechnology, Inc., its affiliates, agents, and employees, and all persons acting on its or their behalf (collectively, "Vishay"), disclaim any and all liability for any errors, inaccuracies or incompleteness contained in any datasheet or in any other disclosure relating to any product.

Vishay makes no warranty, representation or guarantee regarding the suitability of the products for any particular purpose or the continuing production of any product. To the maximum extent permitted by applicable law, Vishay disclaims (i) any and all liability arising out of the application or use of any product, (ii) any and all liability, including without limitation special, consequential or incidental damages, and (iii) any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.

Statements regarding the suitability of products for certain types of applications are based on Vishay's knowledge of typical requirements that are often placed on Vishay products in generic applications. Such statements are not binding statements about the suitability of products for a particular application. It is the customer's responsibility to validate that a particular product with the properties described in the product specification is suitable for use in a particular application. Parameters provided in datasheets and / or specifications may vary in different applications and performance may vary over time. All operating parameters, including typical parameters, must be validated for each customer application by the customer's technical experts. Product specifications do not expand or otherwise modify Vishay's terms and conditions of purchase, including but not limited to the warranty expressed therein.

Hyperlinks included in this datasheet may direct users to third-party websites. These links are provided as a convenience and for informational purposes only. Inclusion of these hyperlinks does not constitute an endorsement or an approval by Vishay of any of the products, services or opinions of the corporation, organization or individual associated with the third-party website. Vishay disclaims any and all liability and bears no responsibility for the accuracy, legality or content of the third-party website or for that of subsequent links.

Except as expressly indicated in writing, Vishay products are not designed for use in medical, life-saving, or life-sustaining applications or for any other application in which the failure of the Vishay product could result in personal injury or death. Customers using or selling Vishay products not expressly indicated for use in such applications do so at their own risk. Please contact authorized Vishay personnel to obtain written terms and conditions regarding products designed for such applications.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted by this document or by any conduct of Vishay. Product names and markings noted herein may be trademarks of their respective owners.

## Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

 [View TCMT1116 on WIN SOURCE](#)

 [Vishay Information](#)

## Optimize Your Supply Chain with WIN SOURCE Solutions

-  Global Sourcing Solution
-  Obsolete Management
-  Cost Control Management
-  Shortage Management
-  Alternative Solution
-  Excess Inventory Management