WINSOURCE ELECTRONICS


THE DATASHEET OF

MA735-(TX)

MA2Q735 (MA735)

Silicon epitaxial planar type

For high frequency rectification



Marking Symbol: PA

■ Features

- Forward current (Average) $I_{F(AV)}$ = 1 A rectification is possible
- Reverse voltage V_R = 30 V is guaranteed
- Automatic insertion with the emboss taping is possible

■ Absolute Maximum Ratings T_a = 25°C


Parameter	Symbol	Rating	Unit
Reverse voltage	V_R	30	V
Maximum peak reverse voltage	V_{RM}	30	V
Forward current (Average) *1	$I_{F(AV)}$	1	A
Non-repetitive peak forward surge current *2	I_{FSM}	30	A
Junction temperature	T_j	−40 to +125	°C
Storage temperature	T_{stg}	−40 to +125	°C

Note) *1: Mounted on the printed circuit board (glass epoxy board)
*2: The peak-to-peak value in one cycle of 50 Hz sine wave (non-repetitive)

■ Electrical Characteristics T_a = 25°C ± 3°C

Parameter	Symbol	Conditions	Min	Typ	Max	Unit
Forward voltage	V_F	I_F = 1.0 A			0.5	V
Reverse current	I_R	V_R = 30 V			1	mA
Terminal capacitance	C_t	V_R = 10 V, f = 1 MHz		50		pF
Reverse recovery time *	t_{rr}	$I_F = I_R$ = 100 mA I_{rr} = 0.1 I_R, R_L = 100 Ω			30	ns


Note) 1. Measuring methods are based on JAPANESE INDUSTRIAL STANDARD JIS C 7031 measuring methods for diodes.
2. This product is sensitive to electric shock (static electricity, etc.). Due attention must be paid on the charge of a human body and the leakage of current from the operating equipment.
3. Absolute frequency of input and output is 20 MHz.
4. *: t_{rr} measurement circuit




Note) The part number in the parenthesis shows conventional part number.

Maintenance/Discontinued
Discontinued includes following four Product lifecycle stages
Planned maintenance type
Planned discontinued type
Discontinued type
Please visit the following URL about the latest information.
http://www.semicon.panasonic.co.jp/en/


I_F — V_F




I_R — V_R




V_F — T_a




I_R — T_a



C_t — V_R



$I_{F(AV)}$ — T_a



Maintenance/Discontinued
Discontinued
Maintenance/Discontinued products followed our Product lifecycle notice.
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/

Request for your special attention and precautions in using the technical information and semiconductors described in this book

(1) If any of the products or technical information described in this book is to be exported or provided to non-residents, the laws and regulations of the exporting country, especially, those with regard to security export control, must be observed.

(2) The technical information described in this book is intended only to show the main characteristics and application circuit examples of the products, and no license is granted under any intellectual property right or other right owned by our company or any other company. Therefore, no responsibility is assumed by our company as to the infringement upon any such right owned by any other company which may arise as a result of the use of technical information described in this book.

(3) The products described in this book are intended to be used for standard applications or general electronic equipment (such as office equipment, communications equipment, measuring instruments and household appliances).
Consult our sales staff in advance for information on the following applications:
- Special applications (such as for airplanes, aerospace, automobiles, traffic control equipment, combustion equipment, life support systems and safety devices) in which exceptional quality and reliability are required, or if the failure or malfunction of the products may directly jeopardize life or harm the human body.
- Any applications other than the standard applications intended.

(4) The products and product specifications described in this book are subject to change without notice for modification and/or improvement. At the final stage of your design, purchasing, or use of the products, therefore, ask for the most up-to-date Product Standards in advance to make sure that the latest specifications satisfy your requirements.

(5) When designing your equipment, comply with the range of absolute maximum rating and the guaranteed operating conditions (operating power supply voltage and operating environment etc.). Especially, please be careful not to exceed the range of absolute maximum rating on the transient state, such as power-on, power-off and mode-switching. Otherwise, we will not be liable for any defect which may arise later in your equipment.
 Even when the products are used within the guaranteed values, take into the consideration of incidence of break down and failure mode, possible to occur to semiconductor products. Measures on the systems such as redundant design, arresting the spread of fire or preventing glitch are recommended in order to prevent physical injury, fire, social damages, for example, by using the products.

(6) Comply with the instructions for use in order to prevent breakdown and characteristics change due to external factors (ESD, EOS, thermal stress and mechanical stress) at the time of handling, mounting or at customer's process. When using products for which damp-proof packing is required, satisfy the conditions, such as shelf life and the elapsed time since first opening the packages.

(7) This book may be not reprinted or reproduced whether wholly or partially, without the prior written permission of Matsushita Electric Industrial Co., Ltd.

Maintenance/Discontinued
Maintenance/Discontinued includes following Products
planed maintenance type
maintenance type
planed discontinued type
discontinued type
Please visit following URL about latest information.
http://www.semicon.panasonic.co.jp/en/

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View MA735-(TX) on WIN SOURCE
- Panasonic Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management