THE DATASHEET OF

TLC2932AIPWR

- **VCO (Voltage-Controlled Oscillator):**
  - **Complete Oscillator Using Only One External Bias Resistor (RBIAS)**
  - **Lock Frequency:**
    13 MHz to 32 MHz (VDD = 3 V ±5%, T_A = –20°C to 75°C, x1 Output)
    13 MHz to 35 MHz (VDD = 3.3 V ±5%, T_A = –20°C to 75°C, x1 Output)
    15 MHz to 55 MHz (VDD = 5 V ±5%, T_A = –20°C to 75°C, x1 Output)
  - **Selectable Output Frequency**
- **PFD (Phase Frequency Detector): High Speed, Edge-Triggered Detector with Internal Charge Pump**
- **Independent VCO, PFD Power-Down Mode**
- **Thin Small-Outline Package (14 Terminal)**
- **CMOS Technology**
- **Pin Compatible TLC2932IPW**

14-PIN TSOP (PW PACKAGE)
(TOP VIEW)



description

The TLC2932A is designed for phase-locked loop (PLL) systems and is composed of a voltage-controlled oscillator (VCO) and an edge-triggered type phase frequency detector (PFD). The oscillation frequency range of the VCO is set by an external bias resistor (R_{BIAS}). The VCO has a 1/2 frequency divider at the output stage. The high speed PFD with internal charge pump detects the phase difference between the reference frequency input and signal frequency input from the external counter. Both the VCO and the PFD have inhibit functions, which can be used as power-down mode. Due to the TLC2932A high speed and stable oscillation capability, the TLC2932A is suitable for use as a high-performance PLL.

AVAILABLE OPTIONS

T_A	PACKAGE
	SMALL OUTLINE (PW)
–20°C to 75°C	TLC2932AIPW

Please be aware that an important notice concerning availability, standard warranty, and use in critical applications of Texas Instruments semiconductor products and disclaimers thereto appears at the end of this data sheet.

PRODUCT PREVIEW information concerns products in the formative or design phase of development. Characteristic data and other specifications are design goals. Texas Instruments reserves the right to change or discontinue these products without notice.

Copyright © 2005, Texas Instruments Incorporated

functional block diagram



Terminal Functions

TERMINAL NAME	TERMINAL NO.	I/O	DESCRIPTION
LOGIC VDD	1		Power supply for the internal logic. This power supply should be separated from VCO V_{DD} to reduce cross-coupling between supplies.
SELECT	2	I	VCO output frequency select. When SELECT is high, the VCO output frequency is ×1/2 and when low. The output frequency is ×1.
VCO OUT	3	O	VCO output. When the VCO INHIBIT is high, VCO output is low.
FIN−A	4	I	Input reference frequency $f_{(REF\ IN)}$ is applied to FIN−A.
FIN−B	5	I	Input for VCO external counter output frequency $f_{(FIN-B)}$. FIN−B is nominally provided from the external counter.
PFD OUT	6	O	PFD output. When the PFD INHIBIT is high, PFD output is in the high-impedance state.
LOGIC GND	7		GND for the internal logic.
TEST	8		Connect to GND.
PFD INHIBIT	9	I	PFD inhibit control. When PFD INHIBIT is high, PFD output is in the high-impedance state.
VCO INHIBIT	10	I	VCO inhibit control. When VCO INHIBIT is high, VCO output is low.
VCO GND	11		GND for VCO.
VCO IN	12	I	VCO control voltage input. Nominally the external loop filter output connects to VCO IN to control VCO oscillation frequency.
RBIAS	13	I	Bias supply. An external resistor (R_{BIAS}) between VCO V_{DD} and R_{BIAS} supplies bias for adjusting the oscillation frequency range.
VCO V_{DD}	14		Power supply for VCO. This power supply should be separated from LOGIC V_{DD} to reduce cross-coupling between supplies.

detailed description

VCO oscillation frequency

The VCO oscillation frequency is determined by an external register (R_{BIAS}) connected between the VCO V_{DD} and the BIAS terminals. The oscillation frequency and range depends on this resister value. For the lock frequency range refer to the recommended operating conditions. Figure 1 shows the typical frequency variation and VCO control voltage.



Figure 1. Oscillation Frequency

VCO output frequency 1/2 divider

The TLC2932A SELECT terminal sets the f_{OSC} VCO output frequency as shown in Table 1. The 1/2 f_{OSC} output should be used for minimum VCO output jitter.

Table 1. VCO Output 1/2 Divider Function

SELLECT	VCO OUTPUT
Low	f_{OSC}
High	1/2 f_{OSC}

VCO inhibit function

The VCO has an externally controlled inhibit function which inhibit the VCO output. A high level on the VCO INHIBIT terminal stops the VCO oscillation and powers down the VCO. The output maintains a low level during the power−down mode as shown in Table 2.

Table 2. VCO Inhibit Function

VCO INHIBIT	VCO OSCILLATOR	VCO OUT	$I_{DD(VCO)}$
Low	Active	Active	Normal
High	Stopped	Low level	Power Down

PFD operation

The PFD is a high-speed, edge-triggered detector with an internal charge pump. The PFD detects the phase difference between two frequency inputs supplied to FIN−A and FIN−B as shown in Figure 2. Normally the reference is supplied to FIN−A and the frequency from the external counter output is fed to FIN−B. For clock recovery PLL system, other types of phase detectors should be used.



Figure 2. PFD Function Timing Chart

PFD inhibit control

A high level on the PFD INHIBIT terminal places PFD OUT in the high-impedance state and the PFD stops phase detection as shown in Table 3. A high level on the PFD INHIBIT terminal can also be used as the power-down mode for the PFD.

Table 3. VCO Output Control Function

PFD INHIBIT	DETECTION	PFD OUT	$I_{DD(PFD)}$
Low	Active	Active	Normal
High	Stopped	Hi−Z	Power Down

VCO block schematic



PFD block schematic



absolute maximum ratings over operating free-air temperature range (unless otherwise noted)†

Supply voltage (each supply), V_{DD} (see Note 1) . . . . . 7 V
Input voltage range (each input), V_{IN} (see Note 1) . . . . . −0.5 V to V_{DD} + 0.5 V
Input current (each input), I_{IN} . . . . . ±20 mA
Output current (each output), I_O . . . . . ±20 mA
Operating free-air temperature range, T_A . . . . . –20°C to 75°C
Storage temperature range, T_{stg} . . . . . –65°C to 150°C

† Stresses beyond those listed under “absolute maximum ratings” may cause permanent damage to the device. These are stress ratings only, and functional operation of the device at these or any other conditions beyond those indicated under “recommended operating conditions” is not implied. Exposure to absolute-maximum-rated conditions for extended periods may affect device reliability.

NOTES: 1. All voltages are with respect to GND.
2. For operation above 25°C free-air temperature, derate linearly at the rate of 5.6 mW/°C.

recommended operating conditions

PARAMETERS		MIN	TYP	MAX	UNIT
Supply voltage (each supply, see Note 3)	V_{DD} = 3 V	2.85	3	3.15	V
	V_{DD} = 3.3 V	3.135	3.3	3.465	
	V_{DD} = 5 V	4.75	5	5.25	
Input voltage, (inputs except VCO IN)		0		V_{DD}	V
Output current, (each output)		0		±2	mA
VCO control voltage at VCO IN		0.9		V_{DD}	V
Lock frequency	V_{DD} = 3 V	13		32	MHz
	V_{DD} = 3.3 V	13		35	
	V_{DD} = 5 V	15		55	
Bias Resisitor	V_{DD} = 3 V	2.2		5.1	kΩ
	V_{DD} = 3.3 V	2.2		5.1	
	V_{DD} = 5 V	2.2		5.1	

NOTE 3: It is recommended that the logic supply terminal (LOGIC V_{DD}) and the VCO supply terminal (VCO V_{DD}) should be at the same voltage and separated from each other.

electrical characteristics, V_{DD} = 3 V, T_A = 25°C (unless otherwise noted)

VCO section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	2.4			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.3	V
V_{TH}	Input threshold voltage at select, VCO inhibit		0.9	1.5	2.1	V
I_I	Input current at Select, VCO inhibit	V_I = V_{DD} or GND			±1	µA
$Z_{I(VCOIN)}$	VCO IN input impedance	VCO IN = 1/2 V_{DD}		10		MΩ
$I_{DD(INH)}$	VCO supply current (inhibit)	See Note 4		0.35	1	µA
$I_{DD(VCO)}$	VCO supply current	See Note 5		8.4	17	mA

NOTES: 4. Current into VCO V_{DD}, when VCO INHIBIT = high, PFD is inhibited.
5. Current into VCO V_{DD}, when VCO IN = 1/2 V_{DD}, R_{BIAS} = 3.3 kΩ, VCOOUT = 15−pF Load, VCO INHIBIT = GND, and PFD INHIBIT = GND.

electrical characteristics, V_{DD} = 3 V, T_A = 25°C (unless otherwise noted) (continued)

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	2.4			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.3	V
I_{OZ}	High impedance state output current	PFD inhibit = high, V_O = V_{DD} or GND			±1	µA
V_{IH}	High level input voltage at Fin−A, Fin−B		2.1			V
V_{IL}	Low level input voltage at Fin−A, Fin−B				0.5	V
V_{TH}	Input threshold voltage at PFD inhibit		0.9	1.5	2.1	
C_{IN}	Input capacitance at Fin−A, Fin−B			5.6		pF
Z_{IN}	Input impedance at Fin−A, Fin−B			10		MΩ
$I_{DD(Z)}$	High impedance state PFD supply current	See Note 6			1	µA
$I_{DD(PFD)}$	PFD supply current	See Note 7			3	mA

NOTES: 6. The current into LOGIC V_{DD} when FIN−A and FIN−B = ground, PFD INHIBIT = V_{DD}, PFD OUT open, and VCO OUT is inhibited.
7. The current into LOGIC V_{DD} when FIN−A = 1 MHz and FIN−B = 1 MHz ($V_{I(PP)}$ = 3 V, rectangular wave), PFD INHIBIT = GND, PFD OUT open, and VCO OUT is inhibited.

operation characteristics, V_{DD} = 3 V, T_A = 25°C (unless otherwise noted)

VCO section

	Parameter	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{OSC}	Operation oscillation frequency	R_{BIAS} = 3.3 kΩ, VCO IN = 1/2 V_{DD}	17	25	33	MHz
f_{STB}	Time to stable oscillation (see Note 8)				10	µs
t_r	Rise time	C_L = 15 pF		9	14	ns
t_f	Fall time	C_L = 15 pF		7.6	12	ns
	Duty cycle at VCO OUT	R_{BIAS} = 3.3 kΩ, VCO IN = 1/2 V_{DD}	45%	50%	55%	
α (f_{OSC})	Temperature coefficient of oscillation frequency	VCO IN = 1/2 V_{DD}, T_A = –20°C to 75°C		–0.264		%/°C
k_{SVS} (fosc)	Supply voltage coefficient of oscillation frequency	VCO IN = 1/2 V_{DD}, V_{DD} = 4.75 V to 5.25 V		0.004		%/mV
	Jitter absolute (see Note 9)	PLL jitter, N = 128		325		ps

NOTES: 8. The time period to the stable VCO oscillation frequency after the VCO INHIBIT terminal is changed to a low level.
9. Jitter performance is highly dependent on circuit layout and external device characteristics. The jitter specification was made with a carefully deigned PCB with no device socket.

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{max}	Maximum operation frequency		17			MH
t_{PLZ}	PFD output disable time from low level			22	50	ns
t_{PHZ}	PFD output disable time from high level			21	50	ns
t_{PZL}	PFD output enable time to low level			6.5	30	ns
t_{PZH}	PFD output enable time to high level			7	30	ns
t_r	Rise time	C_L = 15 pF		3.4	10	ns
t_f	Fall time	C_L = 15 pF		1.9	10	ns

electrical characteristics, V_{DD} = 3.3 V, T_A = 25°C (unless otherwise noted)

VCO section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	2.64			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.33	V
V_{TH}	Input threshold voltage at select, VCO inhibit		1.05	1.65	2.25	V
I_I	Input current at Select, VCO inhibit	$V_I = V_{DD}$ or GND			±1	µA
$Z_{I(VCOIN)}$	VCO IN input impedance	VCO IN = 1/2 V_{DD}		10		MΩ
$I_{DD(INH)}$	VCO supply current (inhibit)	See Note 10		0.38	1	µA
$I_{DD(VCO)}$	VCO supply current	See Note 11		10.8	22	mA

NOTES: 10. Current into VCO V_{DD}, when VCO INHIBIT = high, PFD is inhibited.
11. Current into VCO V_{DD}, when VCO IN = 1/2 V_{DD}, R_{BIAS} = 3.3 kΩ, VCOOUT = 15−pF Load, VCO INHIBIT = GND, and PFD INHIBIT = GND.

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	2.97			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.2	V
I_{OZ}	High impedance state output current	PFD inhibit = high, $V_O = V_{DD}$ or GND			±1	µA
V_{IH}	High level input voltage at Fin−A, Fin−B		2.1			V
V_{IL}	Low level input voltage at Fin−A, Fin−B				0.5	V
V_{TH}	Input threshold voltage at PFD inhibit		1.05	1.65	2.25	
C_{IN}	Input capacitance at Fin−A, Fin−B			5.6		pF
Z_{IN}	Input impedance at Fin−A, Fin−B			10		MΩ
$I_{DD(Z)}$	High impedance state PFD supply current	See Note 12			1	µA
$I_{DD(PFD)}$	PFD supply current	See Note 13			3	mA

NOTES: 12. The current into LOGIC V_{DD} when FIN−A and FIN−B = ground, PFD INHIBIT = V_{DD}, PFD OUT open, and VCO OUT is inhibited.
13. The current into LOGIC V_{DD} when FIN−A = 1 MHz and FIN−B = 1 MHz ($V_{I(PP)}$ = 3.3 V, rectangular wave), PFD INHIBIT = GND, PFD OUT open, and VCO OUT is inhibited.

operation characteristics, V_{DD} = 3.3 V, T_A = 25°C (unless otherwise noted)

VCO section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{OSC}	Operation oscillation frequency	R_{BIAS} = 3.3 kΩ, VCO IN = 1/2 VDD	18	30	43	MHz
fstb	Time to stable oscillation (see Note 14)				10	µs
tr	Rise time	C_L = 15 pF		8.5	14	ns
t_f	Fall time	C_L = 15 pF		7.3	12	ns
f_{DUTY}	Duty cycle at VCO OUT	R_{BIAS}=3.3 kΩ, VCO IN = 1/2 VDD	45	50	55	%
α (f_{OSC})	Temperature coefficient of oscillation frequency	VCO IN = 1/2 VDD, T_A = –20°C to 75°C		–0.28 7		%/°C
k_{SVS}(f_{OSC})	Supply voltage coefficient of oscillation frequency	VCO IN = 1/2 V_{DD}, V_{DD} = 4.75 V to 5.25 V		0.004		%/mV
	Jitter absolute (see Note 15)	PLL jitter, N = 128		245		ps

NOTES: 14. The time period to the stable VCO oscillation frequency after the VCO INHIBIT terminal is changed to a low level.
15. Jitter performance is highly dependent on circuit layout and external device characteristics. The jitter specification was made with a carefully deigned PCB with no device socket.

operation characteristics, V_{DD} = 3.3 V, T_A = 25°C (unless otherwise noted) (continued)

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{max}	Maximum operation frequency		22			MHz
t_{PLZ}	PFD output disable time from low level			21	50	ns
t_{PHZ}	PFD output disable time from high level			21	50	ns
t_{PZL}	PFD output enable time to low level			5.8	30	ns
t_{PZH}	PFD output enable time to high level			6.2	30	ns
t_r	Rise time	C_L = 15 pF		3	10	ns
t_f	Fall time	C_L = 15 pF		1.7	10	ns

electrical characteristics, V_{DD} = 5 V, T_A = 25°C (unless otherwise noted)

VCO section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	4			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.5	V
V_{TH}	Input threshold voltage at select, VCO inhibit		1.5	2.5	3.5	V
I_I	Input current at Select, VCO inhibit	$V_I = V_{DD}$ or GND			±1	µA
$Z_{I(VCOIN)}$	VCO IN input impedance	VCO IN = 1/2 V_{DD}		10		M(
IDD(inh)	VCO supply current (inhibit)	See Note 16		0.56	1	µA
IDD(vco)	VCO supply current	See Note 17		28	50	mA

NOTES: 16. Current into VCO V_{DD}, when VCO INHIBIT = high, PFD is inhibited.
17. Current into VCO V_{DD}, when VCO IN = 1/2 V_{DD}, R_{BIAS} = 3.3 kΩ, VCOOUT = 15−pF Load, VCO INHIBIT = GND, and PFD INHIBIT = GND.

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
V_{OH}	High level output voltage	I_{OH} = –2 mA	4.5			V
V_{OL}	Low level output voltage	I_{OL} = 2 mA			0.2	V
I_{OZ}	High impedance state output current	PFD inhibit = high, $V_O = V_{DD}$ or GND			±1	µA
V_{IH}	High level input voltage at Fin−A, Fin−B		4.5			V
V_{IL}	Low level input voltage at Fin−A, Fin−B				1	V
V_{TH}	Input threshold voltage at PFD inhibit		1.5	2.5	3.5	
C_{IN}	Input capacitance at Fin−A, Fin−B			5.6		pF
Z_{IN}	Input impedance at Fin−A, Fin−B			10		MΩ
$I_{DD(Z)}$	High impedance state PFD supply current	See Note 18			1	µA
$I_{DD(PFD)}$	PFD supply current	See Note 19		0.5	3	mA

NOTES: 18. The current into LOGIC V_{DD} when FIN−A and FIN−B = ground, PFD INHIBIT = V_{DD}, PFD OUT open, and VCO OUT is inhibited.
19. The current into LOGIC V_{DD} when FIN−A = 1 MHz and FIN−B = 1 MHz ($V_{I(PP)}$ = 5 V, rectangular wave), PFD INHIBIT = GND, PFD OUT open, and VCO OUT is inhibited

operation characteristics, V_{DD} = 5 V, T_A = 25°C (unless otherwise noted)

VCO section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{OSC}	Operation oscillation frequency	R_{BIAS} = 3.3 kΩ, VCO IN = 1/2 V_{DD}	37	57	75	MHz
f_{STB}	Time to stable oscillation (see Note 20)				10	us
t_r	Rise time	C_L = 15 pF		7.5	10	ns
t_f	Fall time	C_L = 15 pF		6.4	10	ns
f_{DUTY}	Duty cycle at VCO OUT	R_{BIAS} = 3.3 kΩ, VCO IN = 1/2 V_{DD}	45%	50%	55%	
α (f_{OSC})	Temperature coefficient of oscillation frequency	VCO IN = 1/2 V_{DD}, T_A = –20°C to 75°C		–0.346		%/°C
k_{SVS}(f_{OSC})	Supply voltage coefficient of oscillation frequency	VCO IN = 1/2 V_{DD}, V_{DD} = 4.75 V to 5.25 V		0.002		%/mV
	Jitter absolute (see Note 21)	PLL jitter, N = 128		145		ps

NOTES: 20. The time period to the stable VCO oscillation frequency after the VCO INHIBIT terminal is changed to a low level.
21. Jitter performance is highly dependent on circuit layout and external device characteristics. The jitter specification was made with a carefully deigned PCB with no device socket.

PFD section

	PARAMETER	TEST CONDITIONS	MIN	TYP	MAX	UNIT
f_{max}	Maximum operation frequency		38			MHz
t_{PLZ}	PFD output disable time from low level			20	40	ns
t_{PHZ}	PFD output disable time from high level			20	40	ns
t_{PZL}	PFD output enable time to low level			4	20	ns
t_{PZH}	PFD output enable time to high level			4.3	20	ns
t_r	Rise time	C_L = 15 pF		2.1	10	ns
t_f	Fall time	C_L = 15 pF		1.3	10	ns

PARAMETER MEASUREMENT INFORMATION



Figure 3. VCO Output Voltage Waveform



Figure 4. PFD Output Voltage Waveform

Table 4. PFD Output Test Conditions

PARAMETER	R_L	C_L	S1	S2
t_{PZH}	1 kΩ	15 pF	OPEN	CLOSE
t_{PHZ}				
t_r				
t_{PZL}			CLOSE	OPEN
t_{PLZ}				
t_f				

PARAMETER MEASUREMENT INFORMATION



Figure 5. PFD Output Test Conditions

TYPICAL CHARACTERISTICS



Figure 6.



Figure 7.

TYPICAL CHARACTERISTICS



Figure 8.



Figure 9.



Figure 10.



Figure 11.

TYPICAL CHARACTERISTICS



Figure 12.



Figure 13.



Figure 14.



Figure 15.

TYPICAL CHARACTERISTICS



Figure 16.



Figure 17.



Figure 18.



Figure 19.

TYPICAL CHARACTERISTICS



Figure 20.



Figure 21.



Figure 22.



Figure 23.

TYPICAL CHARACTERISTICS



Figure 24.



Figure 25.



Figure 26.



Figure 27.

TYPICAL CHARACTERISTICS



Figure 28.



Figure 29.

PACKAGING INFORMATION

Orderable Device	Status (1)	Package Type	Package Drawing	Pins	Package Qty	Eco Plan (2)	Lead/Ball Finish (6)	MSL Peak Temp (3)	Op Temp (°C)	Device Marking (4/5)	Samples
TLC2932AIPW	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-20 to 75	Y2932A	Samples
TLC2932AIPWG4	ACTIVE	TSSOP	PW	14	90	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-20 to 75	Y2932A	Samples
TLC2932AIPWR	ACTIVE	TSSOP	PW	14	2000	Green (RoHS & no Sb/Br)	CU NIPDAU	Level-1-260C-UNLIM	-20 to 75	Y2932A	Samples

(1) The marketing status values are defined as follows:
ACTIVE: Product device recommended for new designs.
LIFEBUY: TI has announced that the device will be discontinued, and a lifetime-buy period is in effect.
NRND: Not recommended for new designs. Device is in production to support existing customers, but TI does not recommend using this part in a new design.
PREVIEW: Device has been announced but is not in production. Samples may or may not be available.
OBSOLETE: TI has discontinued the production of the device.

(2) **RoHS:** TI defines "RoHS" to mean semiconductor products that are compliant with the current EU RoHS requirements for all 10 RoHS substances, including the requirement that RoHS substance do not exceed 0.1% by weight in homogeneous materials. Where designed to be soldered at high temperatures, "RoHS" products are suitable for use in specified lead-free processes. TI may reference these types of products as "Pb-Free".
RoHS Exempt: TI defines "RoHS Exempt" to mean products that contain lead but are compliant with EU RoHS pursuant to a specific EU RoHS exemption.
Green: TI defines "Green" to mean the content of Chlorine (Cl) and Bromine (Br) based flame retardants meet JS709B low halogen requirements of <=1000ppm threshold. Antimony trioxide based flame retardants must also meet the <=1000ppm threshold requirement.

(3) MSL, Peak Temp. - The Moisture Sensitivity Level rating according to the JEDEC industry standard classifications, and peak solder temperature.

(4) There may be additional marking, which relates to the logo, the lot trace code information, or the environmental category on the device.

(5) Multiple Device Markings will be inside parentheses. Only one Device Marking contained in parentheses and separated by a "~" will appear on a device. If a line is indented then it is a continuation of the previous line and the two combined represent the entire Device Marking for that device.

(6) Lead/Ball Finish - Orderable Devices may have multiple material finish options. Finish options are separated by a vertical ruled line. Lead/Ball Finish values may wrap to two lines if the finish value exceeds the maximum column width.

Important Information and Disclaimer: The information provided on this page represents TI's knowledge and belief as of the date that it is provided. TI bases its knowledge and belief on information provided by third parties, and makes no representation or warranty as to the accuracy of such information. Efforts are underway to better integrate information from third parties. TI has taken and continues to take reasonable steps to provide representative and accurate information but may not have conducted destructive testing or chemical analysis on incoming materials and chemicals. TI and TI suppliers consider certain information to be proprietary, and thus CAS numbers and other limited information may not be available for release.

In no event shall TI's liability arising out of such information exceed the total purchase price of the TI part(s) at issue in this document sold by TI to Customer on an annual basis.

TAPE AND REEL INFORMATION

REEL DIMENSIONS



TAPE DIMENSIONS



A0	Dimension designed to accommodate the component width
B0	Dimension designed to accommodate the component length
K0	Dimension designed to accommodate the component thickness
W	Overall width of the carrier tape
P1	Pitch between successive cavity centers

TAPE AND REEL INFORMATION

*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Reel Diameter (mm)	Reel Width W1 (mm)	A0 (mm)	B0 (mm)	K0 (mm)	P1 (mm)	W (mm)	Pin1 Quadrant
TLC2932AIPWR	TSSOP	PW	14	2000	330.0	12.4	6.9	5.6	1.6	8.0	12.0	Q1

TAPE AND REEL BOX DIMENSIONS



*All dimensions are nominal

Device	Package Type	Package Drawing	Pins	SPQ	Length (mm)	Width (mm)	Height (mm)
TLC2932AIPWR	TSSOP	PW	14	2000	367.0	367.0	35.0

PW (R–PDSO–G14) PLASTIC SMALL OUTLINE



4040064–3/G 02/11

NOTES:
A. All linear dimensions are in millimeters. Dimensioning and tolerancing per ASME Y14.5M–1994.
B. This drawing is subject to change without notice.
C. Body length does not include mold flash, protrusions, or gate burrs. Mold flash, protrusions, or gate burrs shall not exceed 0,15 each side.
D. Body width does not include interlead flash. Interlead flash shall not exceed 0,25 each side.
E. Falls within JEDEC MO–153

IMPORTANT NOTICE

Texas Instruments Incorporated (TI) reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete.

TI's published terms of sale for semiconductor products (http://www.ti.com/sc/docs/stdterms.htm) apply to the sale of packaged integrated circuit products that TI has qualified and released to market. Additional terms may apply to the use or sale of other types of TI products and services.

Reproduction of significant portions of TI information in TI data sheets is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such reproduced documentation. Information of third parties may be subject to additional restrictions. Resale of TI products or services with statements different from or beyond the parameters stated by TI for that product or service voids all express and any implied warranties for the associated TI product or service and is an unfair and deceptive business practice. TI is not responsible or liable for any such statements.

Buyers and others who are developing systems that incorporate TI products (collectively, "Designers") understand and agree that Designers remain responsible for using their independent analysis, evaluation and judgment in designing their applications and that Designers have full and exclusive responsibility to assure the safety of Designers' applications and compliance of their applications (and of all TI products used in or for Designers' applications) with all applicable regulations, laws and other applicable requirements. Designer represents that, with respect to their applications, Designer has all the necessary expertise to create and implement safeguards that (1) anticipate dangerous consequences of failures, (2) monitor failures and their consequences, and (3) lessen the likelihood of failures that might cause harm and take appropriate actions. Designer agrees that prior to using or distributing any applications that include TI products, Designer will thoroughly test such applications and the functionality of such TI products as used in such applications.

TI's provision of technical, application or other design advice, quality characterization, reliability data or other services or information, including, but not limited to, reference designs and materials relating to evaluation modules, (collectively, "TI Resources") are intended to assist designers who are developing applications that incorporate TI products; by downloading, accessing or using TI Resources in any way, Designer (individually or, if Designer is acting on behalf of a company, Designer's company) agrees to use any particular TI Resource solely for this purpose and subject to the terms of this Notice.

TI's provision of TI Resources does not expand or otherwise alter TI's applicable published warranties or warranty disclaimers for TI products, and no additional obligations or liabilities arise from TI providing such TI Resources. TI reserves the right to make corrections, enhancements, improvements and other changes to its TI Resources. TI has not conducted any testing other than that specifically described in the published documentation for a particular TI Resource.

Designer is authorized to use, copy and modify any individual TI Resource only in connection with the development of applications that include the TI product(s) identified in such TI Resource. NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT OF TI OR ANY THIRD PARTY IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI products or services are used. Information regarding or referencing third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of TI Resources may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI RESOURCES ARE PROVIDED "AS IS" AND WITH ALL FAULTS. TI DISCLAIMS ALL OTHER WARRANTIES OR REPRESENTATIONS, EXPRESS OR IMPLIED, REGARDING RESOURCES OR USE THEREOF, INCLUDING BUT NOT LIMITED TO ACCURACY OR COMPLETENESS, TITLE, ANY EPIDEMIC FAILURE WARRANTY AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY DESIGNER AGAINST ANY CLAIM, INCLUDING BUT NOT LIMITED TO ANY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON ANY COMBINATION OF PRODUCTS EVEN IF DESCRIBED IN TI RESOURCES OR OTHERWISE. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, DIRECT, SPECIAL, COLLATERAL, INDIRECT, PUNITIVE, INCIDENTAL, CONSEQUENTIAL OR EXEMPLARY DAMAGES IN CONNECTION WITH OR ARISING OUT OF TI RESOURCES OR USE THEREOF, AND REGARDLESS OF WHETHER TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.

Unless TI has explicitly designated an individual product as meeting the requirements of a particular industry standard (e.g., ISO/TS 16949 and ISO 26262), TI is not responsible for any failure to meet such industry standard requirements.

Where TI specifically promotes products as facilitating functional safety or as compliant with industry functional safety standards, such products are intended to help enable customers to design and create their own applications that meet applicable functional safety standards and requirements. Using products in an application does not by itself establish any safety features in the application. Designers must ensure compliance with safety-related requirements and standards applicable to their applications. Designer may not use any TI products in life-critical medical equipment unless authorized officers of the parties have executed a special contract specifically governing such use. Life-critical medical equipment is medical equipment where failure of such equipment would cause serious bodily injury or death (e.g., life support, pacemakers, defibrillators, heart pumps, neurostimulators, and implantables). Such equipment includes, without limitation, all medical devices identified by the U.S. Food and Drug Administration as Class III devices and equivalent classifications outside the U.S.

TI may expressly designate certain products as completing a particular qualification (e.g., Q100, Military Grade, or Enhanced Product). Designers agree that it has the necessary expertise to select the product with the appropriate qualification designation for their applications and that proper product selection is at Designers' own risk. Designers are solely responsible for compliance with all legal and regulatory requirements in connection with such selection.

Designer will fully indemnify TI and its representatives against any damages, costs, losses, and/or liabilities arising out of Designer's non-compliance with the terms and provisions of this Notice.

Mailing Address: Texas Instruments, Post Office Box 655303, Dallas, Texas 75265
Copyright © 2018, Texas Instruments Incorporated

Looking for pricing, stock, or lifecycle information?

Click below to explore more details on WIN SOURCE:

- View TLC2932AIPWR on WIN SOURCE
- Texas Instruments Information

Optimize Your Supply Chain with WIN SOURCE Solutions

- Global Sourcing Solution
- Obsolete Management
- Cost Control Management
- Shortage Management
- Alternative Solution
- Excess Inventory Management